



Product Service

Attestation of Conformity

No. E8A 124237 0003 Rev. 00**Holder of Attestation: WUXI XINJE ELECTRIC CO., LTD.**

No. 816, Jianzhu West Road, Binhu District
214026 Wuxi City, Jiangsu Province
PEOPLE'S REPUBLIC OF CHINA

**Name of Object: Servo Motor
AC Servo Motor**

This Attestation of Conformity is issued on a voluntary basis according to the Directive 2014/30/EU relating to electromagnetic compatibility. It confirms that the listed apparatus complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

Test report no.: 4852025263800**Date,** 2025-06-05

(Haifeng Cao)

Page 1 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Product Service

Attestation of Conformity

No. E8A 124237 0003 Rev. 00

Model(s):

MS6A-BCDEFG-HI-J

Remark:

"A" means inertia, can be S, G, H, L:

S: Low inertia, G: Medium inertia,

H: High inertia, L: Ultra-low inertia;

"B" means frame number, can be 40, 60, 80, 130, 180;

"C" means encoder type, can be CS, CM, CN, TL, TH, TX:

CS: 17-bit single turn magneto-electric encoder,

CM: 17 multi-turn magneto-electric encoder,

CN: 19-bit magneto-electric encoder,

TL: 23-bit 2.5M optical-electric encoder,

TH: 23-bit 4M optical-electric encoder,

TX: 26-bit optical-electric encoder;

"D" means rated rotational speed, can be 15, 20, 25, 30:

15: 1500rpm, 20: 2000rpm, 25: 2500rpm, 30: 3000rpm;

"E" means shaft end specification, can be A, B, C, D, E:

A: with keys, no oil seal, with threaded holes,

B: with keys, with oil seals, with threaded holes,

C: no key, no oil seal, with threaded holes,

D: no key, with oil seals, with threaded holes,

E: special shaft specifications (length, shaft diameter, etc.);

"F" means brake, can be blank, Z:

blank: non-brake type, Z: brake payment;

"G" means plug type, can be 1, 2, 3, 4:

1: Amphibious plug, 2: Jacks,

3: Biff, 4: BIFF turns into AMP plug;

"H" means supply voltage/phase, can be 2, 4:

2: 200-240V~/1 phase, 4: 380-440V~/3 phase;

"I" means rated power, can be 0A5, 0P1, 0P2, 0P4, 0P7,

0P8, 1P0, 1P5, 2P3, 3P0, 3P5, 4P4, 5P0, 5P5, 7P5:

0A5: 0.05kW, 0P1: 0.1kW, 0P2: 0.2kW, 0P4: 0.4kW,

0P7: 0.75kW, 0P8: 0.85kW, 1P0: 1.0kW, 1P5: 1.5kW,

2P3: 2.3kW, 3P0: 3.0kW, 3P5: 3.5kW, 4P4: 4.4kW,

5P0: 5.0kW, 5P5: 5.5kW, 7P5: 7.5kW;

"J" means product/client code, can be suffix

"xxxxxxxxxxxxxx", where "x" can be "0-9", "A-Z", "-" or blank.



Product Service

Attestation of Conformity

No. E8A 124237 0003 Rev. 00

Description of Object:

Rated voltage:	200-240V~ (for MS6A-BCDEFG-2I-J) 380-440V~ (for MS6A-BCDEFG-4I-J)
Rated frequency:	50/60Hz
Rated power:	0.05kW (for MS6A-BCDEFG-H0A5-J), 0.1kW (for MS6A-BCDEFG-H0P1-J), 0.2kW (for MS6A-BCDEFG-H0P2-J), 0.4kW (for MS6A-BCDEFG-H0P4-J), 0.75kW (for MS6A-BCDEFG-H0P7-J), 0.85kW (for MS6A-BCDEFG-H0P8-J), 1.0kW (for MS6A-BCDEFG-H1P0-J), 1.5kW (for MS6A-BCDEFG-H1P5-J), 2.3kW (for MS6A-BCDEFG-H2P3-J), 3.0kW (for MS6A-BCDEFG-H3P0-J), 3.5kW (for MS6A-BCDEFG-H3P5-J), 4.4kW (for MS6A-BCDEFG-H4P4-J), 5.0kW (for MS6A-BCDEFG-H5P0-J), 5.5kW (for MS6A-BCDEFG-H5P5-J), 7.5kW (for MS6A-BCDEFG-H7P5-J)

Tested according to:

EN IEC 61000-6-4:2019
EN IEC 61000-6-2:2019
EN IEC 61800-3:2023
EN 60034-1:2010

Page 3 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.