

EtherCAT®

EtherCAT bus More accurate and fast motion control



Servo System DS5/DF3/DM5

Precise control High-speed response Stable and reliable



XINJE Wechat

XINJE

WUXI XINJE ELECTRIC CO.,LTD.

Address: No.816,Jianzhu West Road,Binhu District,Wuxi City,Jiangsu Province,China

TEL: 86-0510-85134136

Website: www.xinje.com

Fax: 86-0510-85111290

Email: sales@xinje.com

Technical Service Hotline
400-885-0136

Industrial automation trusted partner

Servo System Overview

Small-sized Servo System

At present, the small volume servo system has four subseries products of pulse type and bus type. In addition to all the functions of the general series, its outstanding advantage is that it is smaller and can save more installation space.

Applicable to 3C, textile, printing, packaging, food, medicine, electronics, environmental protection and other fields.

Adaptive motor: MS5, MS6 series.

Bus type	DS5C1	0.1kW~55kW	EtherCAT
	DS5N1	0.1kW~3kW	CANopen
Pulse type	DS5L1	0.1kW~3kW	Modbus
	DS5K1	11kW~15kW	Modbus



General Servo System

The general servo system has a complete product line, including five subseries of pulse type, bus type and full-function type. It has the characteristics of high-speed response, accurate synchronization, rapid adjustment, convenience and ease of use.

Suitable for a variety of applications.

Adaptive motor: MS5, MS6 series.

Bus type	DS5C	0.1kW~32kW	EtherCAT
	DS5E	0.1kW~22kW	X-NET
Pulse type	DS5L	0.1kW~2.6kW	Modbus
	DS5K	0.1kW~7.5kW	Modbus
Full-function type	DS5F	0.1kW~7.5kW	Modbus



*Note: Refer to the model list for the models that have been put into production. Please look forward to the development of some models.

Two-in-one Servo System

At present, the two-in-one series servo system has a pulse type subseries product. It has outstanding advantages such as flat appearance, dual-axis integrated drive, convenient wiring and accurate positioning. It has built-in gantry synchronous control, which can meet the accuracy requirements under high-speed movement.

Suitable for sewing, wire cutting, laser cutting, printing, turret punch and other equipment.

Adaptive motor: MS5, MS6 series.

Pulse type	DM5F	0.4kW~0.75kW	Modbus
------------	------	--------------	--------



Low Voltage Servo System

At present, the low-voltage servo system has a bus type subseries. It has compact design, light weight body, rich interfaces, supports communication protocols such as CANopen and Modbus, low-voltage DC power supply, with 24V brake power output, and only three steps for gain adjustment, which reduces the debugging time.

It is applicable to AGV, sorting, logistics, warehousing and medical fields.

Adaptive motor: MF3 series.

Bus type	DF3E	0.4kW~1.5kW	CANopen
----------	------	-------------	---------



*Note: Refer to the model list for the models that have been put into production. Please look forward to the development of some models.

General/Small-sized servo system

Stable and easy to use / Excellent performance
High-speed response / Rich product lineup

Suitable for: wire cutting,packaging, textile, woodworking, labeling and other applications



Small-sized Series



Bus type	DS5C1	EtherCAT, RS232, 3-channel SI, 3-channel SO, Position mode, Speed mode, Torque mode, Bus mode
	DS5N1	CANopen, RS232, 3-channel SI, 3-channel SO, Position mode,Speed mode, Torque mode, Bus mode
Pulse type	DS5L1	Pulse, RS232, RS485, 3-channel SI, 3-channel SO, Position mode, speed mode, torque mode
	DS5K1	Pulse, Analog input, RS485, RS232, 3-channel SI, 3-channel SO, Position mode, Speed mode Torque mode

General Series



Bus type	DS5C	Pulse, RS232, 4 or 3 channels SI, 4 or 3 channels SO, Position mode, Speed mode, Torque mode, Bus mode
	DS5E	Pulse, RS232, RS485, 4 or 3 channels SI, 4 or 3 channels SO, Position mode, Speed mode, Torque mode, Bus mode
Pulse type	DS5L	Pulse, RS232, 4 or 3 channels SI, 4 or 3 channels SO, Position mode, Speed mode, Torque mode
	DS5K	Pulse, RS232, 5 channels SI, 4 channels SO, Position mode, Speed mode, Torque mode
Full-function type	DS5F	Pulse, Line driver, Analog input, External displacement sensor, RS232, RS485, 10 channels SI, 8 channels SO, Position mode, Speed mode, Torque mode, Analog control, Full closed-loop control

MS6,MS5 Series Servo Motor



High inertia	Occasions with large load and high stability requirements MS6H 0.1~7.5kW
Medium inertia	Occasions with general load and high stability requirements MS5G 0.85~22kW MS6G 0.85~2.3kW
Low inertia	Occasions with light load and high-speed positioning requirements MS6S 0.4~2.0kW

*Note: The models above 750W have 4 channels of SI/SO. The models below and equal to 750W have 3 channels of SI/SO.

MS6,MS5 Series Servo Motor

High protection grade
High-precision positioning

Light weight design



1 New Appearance and Structure


MS6 series B3 motor

- The new black body with frosted texture can effectively reduce the tactile temperature of the motor.



2 Low Noise&Light Temperature Rise

- Effective noise reduction. Compared with the previous motor, the winding temperature rise of B3 motor can be reduced by 20°C (take 400W as an example).



3 Higher Protection Level

- The structure of MS6 series motor is optimized to further improve the protection grade. The protection grade of B1/B2 series can reach IP66 and B3 series can reach IP67.




4 Motor is light and handy

- The body of MS6 series motor is further shortened, which can be shortened by 18% compared with MS5 series motor.




5 Higher Torque Output

- At present, the speed of MS6 series 400W motor can be overspeed to 6500rpm, and the maximum speed still maintains 80% of the rated output.




6 Wider Overspeed Range

- MS6 series flange 180 motor can overspeed up to 3000rpm, which is 20% higher than MS5 series.




7 Encoder resolution

- The whole series is equipped with 17-bit encoder as standard, and 23-bit encoder is optional.
- Achieve higher precision position control and stable operation at low speed.
- The anti-oil and vibration ability of magnetic encoder is enhanced.



8 Flexible Configuration to Meet Different Needs

- Low inertia, medium inertia and high inertia motors are available.
- It can be equipped with power loss brake, oil seal, etc.
- B3 series front and rear outgoing cables are optional.
- B3 series can be configured with connector to amp adapter.



DS5 Series Servo Drive

Precise synchronization
Rapid adjustment


High-speed response
Easy to use



1 Smaller Size, Saving Installation Space


- The size is about 10% thinner than the previous generation.
- Save installation space.

Note: The figure shows the comparison of DS5L 750W and DS5L1 750W.




2 High Speed Response

- The rigid gain adjustment mode of servo system is self-tuning mode, which no need complicated adjustment process and greatly saves debugging time.
- By further gain adjustment, the positioning completion time can be reduced to 0 ~ 10ms.




3 Quick Adjustment to Shorten Positioning Time

- Load inertia estimation, find the optimal gain, and the positioning completion time is within 20ms.
- The drive panel is adjusted offline.
- 63 rigidity grades.




5 Active/Manual Vibration Suppression

- Support 1-channel active vibration suppression.
- Equipped with 5 notch filters, combined with the vibration mechanical characteristic analysis function, the vibration suppression ability is improved.
- The filter setting frequency is 50 ~ 5000Hz, and the depth can be adjusted.
- Optimize friction compensation and disturbance observation algorithm.




4 High Speed Pulse Input

- DS5F supports 2Mpps long line reception.
- The full range of drives supports 200kpps (collector input) and DS5F/DS5K/DS5L1/DS5K1 series drives support 500kpps (differential input).



6 S-type Acceleration and Deceleration Curve

- S-type acceleration and deceleration curve can effectively overcome the mechanical vibration caused by sudden speed change, making the motion softer and more stable.



7 Wide Power Coverage


- New high-power models are added for small volume servo, and the power range is from 100W to 55kW.



*Note: Please refer to the model list for the product that have been put into operation, and some models are under development.

8 Full Closed-Loop Input DS5F Series

- Reduce mechanical disturbance and determine the positioning of mechanical load terminal to ensure positioning accuracy.




EtherCAT Bus

100 megabytes full duplex Ethernet reduces the networking cost and makes the system structure more flexible




1 Synchronous Clock

- Through the precise adjustment of EtherCAT distributed clock, the distance of 300 nodes 120m, 15ns synchronization error and ± 20 ns synchronization jitter are realized.
- Transmission rate: 2×100Mbps (full duplex)




2 High Speed Response

- Support 2-channel high speed touch probe function.
- Response time can up to 1ms.



3 Network Topology to Reduce Cabling Costs

- The standard RJ45 Industrial Ethernet fast interface is adopted to greatly reduce the labor cost and time consumption of wiring.



4 EtherCAT Networking Debugging


- For EtherCAT networking equipment, the user can read or write all servo axes parameters at one time through the servo software, and can save the complete equipment recipe.



Typical Application


One to one high-speed plane mask machine

The mask machine is to manufacture various masks with certain filtering performance by hot pressing, folding and forming, ultrasonic welding, waste cutting, ear belt and nose beam welding and other processes of multi-layer non-woven fabrics. The mask equipment is not a single machine, but needs the cooperation of multiple machines to complete various different processes. The system of one to one mask machine is composed of constant tension feeding mechanism, sheet feeding mechanism and ear welding mechanism.



Mechanical arm

Manipulator is the most widely used automatic mechanical device in the field of robotics. It can be seen in industrial manufacturing, medical treatment, entertainment services, military, semiconductor manufacturing and space exploration. Although their shapes are different, they all have a common feature, that is, they can accept instructions and accurately locate a point in 3D (or 2D) space for operation.



High speed cutting machine

The high-speed cutting machine combines the ultrasonic welding technology with the traditional cutting. When the ultrasonic generator works, the ultrasonic energy is transmitted to the welding head through the ultrasonic transducer and generates violent vibration and friction with the cutter, so as to achieve the cutting effect, so that the cutting products have the advantages of more beauty, firmness, more efficient and fast production efficiency.




Circular die cutting machine

Circular die cutting machine is one of the most efficient cutting machines, which rotates continuously in the form of hob for cutting. Round knife cutting achieves the purpose of die cutting by extruding materials through the blade and backing roller. On the one hand, it improves the speed and accuracy of die cutting. On the other hand, it can form one-time products through multi-shaft sleeve position die cutting, which makes up for the disadvantage of traditional multiple die cutting.



16 axes high speed winding machine

High speed winding machine is a device that winds linear objects to a specific workpiece. It is usually used for copper wire winding. In the past, it used to realize high-speed winding through variable-frequency motor combined with tension control system. With the increasing demand for benefits in modern industry, it can replace the original variable-frequency motor with servo to realize high-speed and high-efficiency production.



Three-servo packaging machine

Packaging machinery refers to the machinery that can complete the packaging process of all or part of products and commodities. The packaging process includes filling, wrapping, sealing and other main processes, as well as related before and after processes, such as cleaning, stacking and disassembly. In addition, packaging also includes measuring or stamping on the package. The use of mechanical packaging products can improve productivity, reduce labor intensity, meet the needs of large-scale production and meet the requirements of cleanliness and hygiene.



XINJE SERVO Software


Help users better understand the operation of the equipment



1 Servo Communication Interface

Efficient and fast communication identification

XINJE servo software can do Modbus-RTU communication with servo driver through RS232, and can automatically read motor parameters without viewing motor code.



2 Parameter Setting Interface

Intuitive and understandable parameter setting

XINJE servo software has the functions of reading, modifying, saving and downloading, and is equipped with detailed parameter description. The parameter list directly indicates the effective time of parameters with different colors, which makes the distinction more eye-catching.



3 Curve Acquisition Interface

Convenient and practical curve acquisition


XINJE servo software has powerful servo data acquisition function, including speed, position, current, bus voltage and other basic information acquisition. Help you have a deeper and comprehensive understanding of servo operation and improve the control scheme.



4 Real Time Observation Interface

Real time dynamic curve observation


XINJE servo software can collect basic information such as speed, torque, position and bus voltage to help you understand the servo operation in real time and adjust the control scheme efficiently and timely.



5 Parameter Comparison Interface

Simple and clear parameter comparison


The parameter comparison function of XINJE servo software allows customers to easily compare preset values, current driver values, file values, and pairwise comparison of the current upper computer interface.



6 Mechanical Property Measurement Interface

Precise resonance recognition


XINJE software has the function of mechanical characteristic measurement, which can automatically measure the resonance frequency according to the operation of mechanical load. It is equipped with five notch filters to ensure the stable and reliable operation of the equipment and sweep away the load vibration.




7 Gain Adjustment Interface

Fast adjustment

The fast adjustment / self-tuning mode can identify the inertia. The user can configure the appropriate mode, method, load type, foundation and other parameters according to the equipment operation status for the upper computer to set the best gain parameters, or adjust the rigidity level according to the equipment operation status.




Self-tuning interface



5 Monitor Interface

Rich and comprehensive real-time monitoring


XINJE servo software has real-time status, alarm monitor and servo operation status, which are all under your control.



6 Tool Interface


Motor selection tool

XINJE servo software has its own motor selection tool, which automatically matches the best motor model through the selection of equipment components and the establishment of motion model.



Electronic gear ratio conversion

XINJE servo software can accurately calculate the number of pulses per revolution and electronic gear ratio of screw, disc and pulley mechanical structures according to the mechanical specifications.



Naming Rule

MS6 motor naming rule

MS6S - 60 C S 30 B Z 1 - 2 0P4

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

① Inertia type		② Base number		③ Encoder construction		④ Encoder specification		⑩ Rated power	
Sign	Inertia	Sign	Base number	Sign	Type	Sign	Specification	Sign	Rated power (kW)
MS6S	Low inertia motor	40	Base40	C	Magnetic encoder	S	Single turn 17-bit	0P1	0.1
MS6G	Medium inertia motor	60	Base60	T	Photoelectricity encoder	M	Multi-turn 17-bit	0P2	0.2
MS6H	High inertia motor	80	Base80			L	Multi-turn 23-bit	0P4	0.4
		100	Base100					0P7	0.75
		130	Base130					0P8	0.85
		180	Base180					1P0	1
								1P3	1.3
								1P5	1.5
								1P8	1.8
								2P0	2.0
								2P3	2.3
								3P0	3.0
								4P4	4.4
								5P5	5.5
								7P5	7.5
								22P0	22
								30P0	30
								37P0	37
								45P0	45
								55P0	55

⑤ Rated speed		⑧ Motor connector type	
Sign	Rated speed (rpm)	Sign	Connector type
15	1500	1	AMP plug
20	2000	2	Aviation plug
25	2500	3	Connector
30	3000		

⑥ Motor shaft specification		⑨ Power supply voltage	
Sign	Shaft specification	Sign	Power supply voltage
A	With key, no oil seal, with threaded hole	2	220V
B	With key, with oil seal, with threaded hole	4	380V
C	No key, no oil seal, with threaded hole		
D	No key, with oil seal, with threaded hole		
E	Special shaft specification (length, shaft diameter, etc.)		

⑦ Power-off brake	
Sign	Power-off brake
Z	With brake
Vacant	Without brake

*Note: The description provided is only an example. Refer to the detailed parameters of the motor for the specific model. Our company provides combined models of CS, CM and TL.

MS5 motor naming rule

MS5G - 130 ST E - C S 11515 B Z - 2 1P8 - S01

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪ ⑫

① Inertia type		② Base number		③ Name		④ Motor structure		⑤ Encoder construction	
Sign	Inertia	Sign	Base number	Sign	Type	Sign	Oil seal	Sign	Type
MS5S	Low inertia motor	110	Base 110	ST	Sine wave drive motor	Vacant	No oil seal	C	Magnetic encoder
MS5G	Medium inertia motor	130	Base 130	E	With oil seal	E	With oil seal	T	Photoelectricity encoder
		220	Base 220						

⑥ Encoder specification		⑨ Power-off brake	
Sign	Specification	Sign	Connector type
S	Single turn 17-bit	Vacant	Without brake
M	Multi-turn 17-bit	Z	With brake
L	Multi-turn 23-bit		

⑦ Motor specification		⑩ Power supply voltage	
Sign	Rated torque (Nm)	Sign	Power supply voltage
04830	0.48	2	220V
11515	11.5	4	380V

⑧ Motor construction		⑪ Rated power	
Sign	Shaft key	Sign	Rated power (kW)
B	With key	1P0	1.0
		1P5	1.5
		1P8	1.8
		2P3	2.3
		22P0	22

⑫ Design number	
Sign	Meaning
S	Standard
01	Design number

*Note: The description provided is only an example. Refer to the detailed parameters of the motor for the specific model. Our company provides combined models of CS, CM, TL and T.

DS5 servo drive naming rule

DS 5 - P - PTA-H

① ② ③ ④ ⑤ ⑥

① Name		② Type		④ Drive power		④ Drive power	
Sign	Product name	Sign	Product series	Sign	Rated output power (kW)	Sign	Rated output power (kW)
DS	Servo drive	5C	EtherCAT bus type	0P1	0.1	32P0	32
		5E	X-NET bus type	0P2	0.2	37P0	37
		5F	Full function type	0P4	0.4	45P0	45
		5K	Standard type	0P7	0.75	55P0	55
		5L	Pulse type	1P0	1.0		
		5C1	Small size bus type	1P5	1.5		
		5L1	Small size pulse type	2P3	2.3		
		5K1	Small size standard type	2P6	2.6		
		5N1	Small size CANopen type	3P0	3.0		
				4P5	4.5		
				5P5	5.5		
				7P5	7.5		
				11P0	11		
				15P0	15		
				22P0	22		

③ Voltage specification		⑥ Product type	
Sign	Rated input voltage	Sign	Product type
2	AC220V	H	Enhanced type drive
4	AC380V		

⑤ Encoder specification	
Sign	Encoder specification
T	Communication type encoder

Motor and drive specifications

MS6/MS5 Motor																	
Item	100W	200W	400W	750W	850W	1.0kW	1.3kW	1.5kW	1.8kW	2.3kW	2.4kW	2.6kW	3.0kW	4.4kW	5.5kW	7.5kW	22kW
Low inertia MS6S			60	80		80											
Medium inertia MS6G						130				130							
High inertia MS6H	40	60	60	80	130	80	130	130	130	130			180	180	180	180	265
Low inertia MS5S								110	110								265
Medium inertia MS5G					130			130	130	130	130	130					220

*Note: 40/60/80/110/130/180/220/265 indicates the motor flange. Provide models with voltage grade of 220V. Provide models with voltage grade of 380V. The motor marked with * is still under development. Please look forward to it. Provide models with voltage grade of 220V/380V.

DS5 drive specification													
Function	Control mode				Control mode								
	Position control	Speed control	Torque control	Bus control	Pulse	Line driver	Analog input	External displacement sensor	ABZ differential feedback	RS232	RS485	SI input	SO output
Pulse type DS5L series	●	●	●		●					●		4	4
EtherCAT type DS5C series	●	●	●	●	●					●		4	4
Xnet bus type DS5E series	●	●	●	●	●					●	●	4	4
Full function type DS5F series	●	●	●		●	●	●	●	●	●	●	10	8
Standard type DS5K series	●	●	●		●				●	●	●	5	4
Pulse type DS5L1 series	●	●	●		●					●	●	3	3
EtherCAT type DS5C1 series	●	●	●	●						●		3	3
Standard type DS5K1 series	●	●	●		●		●		●	●	●	5	4
CANopen type DS5N1 series	●	●	●	●						●		3	3

*Note: DS5E, DS5L, DS5C series 750W and below power models are 3 inputs and 3 outputs.

Drive and Motor Model List

MS6 series motor model list

Power (kW)	Motor model	Flange (mm)	Rated speed (rpm)	Rated torque (Nm)	Inertia type	Encoder bits
0.1	MS6H-40CS/CM/TL30B(Z)1/2/3-20P1	40	3000	0.32	High inertia	17/23
0.2	MS6H-60CS/CM/TL30B(Z)1/2/3-20P2	60	3000	0.64	High inertia	17/23
0.4	MS6S-60CS/CM/TL30B(Z)1/2/3-20P4	60	3000	1.27	Low inertia	17/23
	MS6H-60CS/CM/TL30B(Z)1/2/3-20P4		3000	1.27	High inertia	17/23
0.75	MS6S-80CS/CM/TL30B(Z)1/2/3-20P7	80	3000	2.39	Low inertia	17/23
	MS6H-80CS/CM/TL30B(Z)1/2/3-20P7		3000	2.39	High inertia	17/23
	MS6S-80CS/CM20B(Z)1/2-20P7		2000	3.50	High inertia	17/23
	MS6H-80CS/CM20B(Z)1/2-20P7		2000	3.50	High inertia	17/23
0.85	MS6H-130CS/CM/TL15B(Z)2-20P8	130	1500	5.41	High inertia	17/23
	MS6H-130CS/CM/TL15B(Z)2-40P8		1500	5.41	High inertia	17/23
1	MS6S-80CS/CM/TL30B(Z)3-21P0	80	3000	3.18	Low inertia	17/23
	MS6H-80CS/CM/TL30B(Z)3-21P0		3000	3.18	High inertia	17/23
	MS6G-130CS/CM/TL25B(Z)2-41P0*	130	2500	4.0	Medium inertia	17/23
1.3	MS6H-130CS/CM/TL15B(Z)2-41P3	130	1500	8.30	High inertia	17/23
1.5	MS6S-100CS/CM/TL30B(Z)2-21P5	100	3000	4.8	Low inertia	17/23
	MS6H-130CS/CM/TL20B(Z)2-21P5	130	2000	7.16	High inertia	17/23
	MS6G-130CS/CM/TL20B(Z)2-41P5*		2000	7.16	Medium inertia	17/23
	MS6G-130CS/CM/TL15B(Z)2-41P5*		1500	10.0	Medium inertia	17/23
1.8	MS6H-130CS/CM/TL15B(Z)2-21P8	130	1500	11.46	High inertia	17/23
	MS6H-130CS/CM/TL15B(Z)2-41P8	130	1500	11.46	High inertia	17/23
2.3	MS6H-130CS/CM/TL15B(Z)2-22P3	130	1500	14.64	High inertia	17/23
	MS6G-130CS/CM/TL15B(Z)2-42P3*		1500	14.64	High inertia	17/23
3.0	MS6H-180CS/CM15B(Z)2-43P0	180	1500	19.0	High inertia	17/23
4.4	MS6H-180CS/CM/TL15B(E)2-44P4		1500	28.0	High inertia	17/23
5.5	MS6H-180CS/CM/TL15B(E)2-45P5		1500	35.0	High inertia	17/23
7.5	MS6H-180CS/CM/TL15B(E)2-47P5		1500	47.8	High inertia	17/23
30	MS6H-265TL15B2-430P0*	265	1500	191.0	High inertia	23
37	MS6H-265TL15B2-437P0*	265	1500	236.0	High inertia	23
45	MS6H-265TL15B2-445P0*	265	1500	286.0	High inertia	23
55	MS6H-265TL15B2-455P0*	265	1500	350.0	High inertia	23

*Note: 1. B(Z) indicates brake model can be selected, non-brake model code is B, brake model code is BZ.
2. The servo driver marked with * is still under development. Please look forward to it.
3. Please select engineering aviation plug for motors below 60/80.

MS5 series motor model list

Power (kW)	Motor model	Flange (mm)	Rated speed (rpm)	Rated torque (Nm)	Inertia type	Encoder bits
0.85	MS5G-130STE-CS/CM05415B-20P8-S01	130	1500	5.4	Medium inertia	17
	MS5G-130STE-CS/CM05415BZ-20P8-S01		1500	5.4	Medium inertia	17
	MS5G-130STE-TL05415B-20P8-S01		1500	5.4	Medium inertia	23
	MS5G-130STE-TL05415BZ-20P8-S01		1500	5.4	Medium inertia	23
1.0	MS5S-110STE-CS/CM03230B□-21P0-S01	110	3000	3.18	Low inertia	17
	MS5S-110STE-TL03230B□-21P0		3000	3.18	Low inertia	23
1.5	MS-110STE-T05030B□-21P5		3000	5	/	17
	MS5S-110STE-CS/CM04830B□-21P5-S01		3000	4.77	Low inertia	17
	MS5S-110STE-TL04830B□-21P5-S01		3000	4.77	Low inertia	23
	MS5G-130STE-CS/CM06025B□-21P5-S01	130	2500	6	Medium inertia	17
	MS5G-130STE-CS/CM/TL07220B□-21P5-S01		2000	7.2	Medium inertia	17/23
	MS5G-130STE-CS/CM/TL07220B□-41P5-S01		2000	7.2	Medium inertia	17/23
1.8	MS5G-130STE-CS/CM10015B□-21P5-S01		1500	10	Medium inertia	17
	MS5G-130STE-CS/CM11515B□-21P8-S01	130	1500	11.5	Medium inertia	17
	MS5G-130STE-TL11515B□-21P8-S01		1500	11.5	Medium inertia	23
	MS5G-130STE-CS/CM11515B□-41P8-S01		1500	11.5	Medium inertia	17
	MS5G-130STE-TL11515B□-41P8-S01		1500	11.5	Medium inertia	23
	MS5S-110STE-TL06030B□-21P8-S01	110	3000	6	Low inertia	23
	MS5S-110STE-CS/CM06030B□-21P8-S01		3000	6	Low inertia	17
2.3	MS5G-130STE-CS/CM14615B□-22P3-S01	130	1500	14.6	Medium inertia	17
	MS5G-130STE-TL14615B□-22P3-S01		1500	14.6	Medium inertia	23
	MS5G-130STE-CS/CM14615B□-42P3-S01		1500	14.6	Medium inertia	17
	MS5G-130STE-TL14615B□-42P3-S01		1500	14.6	Medium inertia	23
2.4	MS5G-130STE-CS/CM/TL07730B□-22P4-S01	220	3000	7.7	Medium inertia	17/23
2.6	MS5G-130STE-CS/CM/TL10025B□-22P6-S01		2500	10	Medium inertia	17/23
3.0	MS-130ST-TL10030B□-43P0		3000	10	/	23
11	MS-220STE-TL70015B-411P0-XJ	220	1500	70	/	23
15	MS-220STE-TL96015B-415P0-XJ		1500	96	/	23
22	MS5G-220STE-CS/CM/TL140015B-422P0-S01		1500	140	Medium inertia	17/23

*Note: 1. B□ indicates brake model can be selected, brake model code is BZ, non-brake model code is B.
2. CS/CM indicates single turn magnetic encoder CS or multi-turn magnetic encoder CM can be selected.
3. Flange 110 and up code S01 motors are aviation plug.
4. For other detailed motor characteristic parameters, please refer to the electrical parameters and dimensions on the next page.


DS5 series drive model list

Series	DS5E series	DS5C series	DS5F series	DS5K series	DS5L series	DS5L1 series	DS5C1series	DS5N1 series	DS5K1 series
Power (kW)	X-NET bus type	EtherCAT bus type	full function type	standard type	pulse type	small size pulse type	small size bus type	small size bus type	small size standard type
0.1	DS5E-20P1-PTA	DS5C-20P1-PTA	DS5F-20P1-PTA	DS5K-20P1-PTA	DS5L-20P1-PTA	DS5L1-20P1-PTA	DS5C1-20P1-PTA	DS5N1-20P1-PTA	DS5K1-20P1-PTA*
0.2	DS5E-20P2-PTA	DS5C-20P2-PTA	DS5F-20P2-PTA	DS5K-20P2-PTA	DS5L-20P2-PTA	DS5L1-20P2-PTA	DS5C1-20P2-PTA	DS5N1-20P2-PTA	DS5K1-20P2-PTA*
0.4	DS5E-20P4-PTA	DS5C-20P4-PTA	DS5F-20P4-PTA	DS5K-20P4-PTA	DS5L-20P4-PTA	DS5L1-20P4-PTA	DS5C1-20P4-PTA	DS5N1-20P4-PTA	DS5K1-20P4-PTA*
0.75	DS5E-20P7-PTA	DS5C-20P7-PTA	DS5F-20P7-PTA	DS5K-20P7-PTA	DS5L-20P7-PTA	DS5L1-20P7-PTA	DS5C1-20P7-PTA	DS5N1-20P7-PTA	DS5K1-20P7-PTA*
1.0	DS5E-21P0-PTA	DS5C-21P0-PTA	DS5F-21P0-PTA	DS5K-21P0-PTA	DS5L-21P0-PTA	DS5L1-21P0-PTA*	DS5C1-21P0-PTA*	/	/
1.5	DS5E-21P5-PTA	DS5C-21P5-PTA	DS5F-21P5-PTA	DS5K-21P5-PTA	DS5L-21P5-PTA	DS5L1-21P5-PTA*	DS5C1-21P5-PTA*	/	/
2.3	DS5E-22P3-PTA	DS5C-22P3-PTA	DS5F-22P3-PTA	DS5K-22P3-PTA	DS5L-22P3-PTA	DS5L1-22P3-PTA*	DS5C1-22P3-PTA*	/	/
2.6	DS5E-22P6-PTA	DS5C-22P6-PTA	DS5F-22P6-PTA	DS5K-22P6-PTA	DS5L-22P6-PTA	DS5L1-22P6-PTA*	/	/	/
1	DS5E-41P0-PTA	DS5C-41P0-PTA	DS5F-41P0-PTA	DS5K-41P0-PTA	/	/	DS5C1-41P0-PTA*	/	/
1.5	DS5E-41P5-PTA	DS5C-41P5-PTA	DS5F-41P5-PTA	DS5K-41P5-PTA	/	/	DS5C1-41P5-PTA*	/	/
2.3	/	/	/	/	/	/	DS5C1-42P3-PTA*		
3	DS5E-43P0-PTA DS5E-43P0-PTA-H	DS5C-43P0-PTA DS5C-43P0-PTA-H	DS5F-43P0-PTA DS5F-43P0-PTA-H	DS5K-43P0-PTA	/	/	DS5C1-43P0-PTA*	/	/
5.5	DS5E-45P5-PTA DS5E-45P5-PTA-H	DS5C-45P5-PTA DS5C-45P5-PTA-H	DS5F-45P5-PTA DS5F-45P5-PTA-H	/	/	/	DS5C1-45P5-PTA*	/	/
7.5	DS5E-47P5-PTA DS5E-47P5-PTA-H	DS5C-47P5-PTA DS5C-47P5-PTA-H	DS5F-47P5-PTA DS5F-47P5-PTA-H	/	/	/	DS5C1-47P5-PTA*	/	/
11	DS5E-411P0-PTA	DS5C-411P0-PTA	/	/	/	/	DS5C1-411P0-PTA	/	DS5K1-411P0-PTA
15	DS5E-415P0-PTA	DS5C-415P0-PTA	/	/	/	/	DS5C1-415P0-PTA	/	DS5K1-415P0-PTA
22	DS5E-422P0-PTA	DS5C-422P0-PTA	/	/	/	/	DS5C1-422P0-PTA	/	/
32	/	DS5C-432P0-PTA	/	/	/	/	DS5C1-432P0-PTA	/	/
37	/	/	/	/	/	/	DS5C1-437P0-PTA	/	/
45	/	/	/	/	/	/	DS5C1-445P0-PTA	/	/
55	/	/	/	/	/	/	DS5C1-455P0-PTA	/	/

*Note: The servo driver marked with * is still under development. Please look forward to it.


Peripheral Connection

DS5 series



Terminal Definition

DS5L1/DS5C1/DS5N1 series



① RS-232 port [DS5L1/5C1/5N1]

Pin	Name	Explanation
1	TXD	RS232 send
2	RXD	RS232 send
3	GND	RS232 signal ground

④ CN1 port [DS5C1]

Pin	Name	Explanation
1	TX A+	TRANSMIT A+
2	TX A-	TRANSMIT A-
3	RX A+	RECEIVE A+
4	/	/
5	/	/
6	RX A-	RECEIVE A-
7	/	/
8	/	/
9	X B+	TRANSMIT B+
10	TX B-	TRANSMIT B-
11	RX B+	RECEIVE B+
12	/	/
13	/	/
14	RX B-	RECEIVE B-
15	/	/
16	/	/

CN1 port [DS5N1]

No.	Name	No.	Name
1	CAN_H	9	CAN_H
2	CAN_L	10	CAN_L
3	CAN_GND	11	CAN_GND
4	/	12	/
5	/	13	/
6	/	14	/
7	/	15	/
8	/	16	/

② Main circuit terminal definition [DS5L1/DS5C1/DS5N1]

Terminal	Function	Explanation
L/N	Main circuit power supply input terminal	single phase AC200~240V, 50/60Hz
•	Vacant terminal	/
P+/C	Use external regenerative resistor	Connect the regeneration resistance to terminals P+ and C, P0-25 = power value, P0-26 = resistance value
U/V/W/PE	Motor connection terminal	Connect to the motor

750W

Terminal	Function	Explanation
L/N	Main circuit power supply input terminal	Single phase AC200~240V, 50/60Hz
•	Vacant terminal	/
P+/D/C	Use built-in regenerative resistor	Short connect P+ and D terminals, disconnect P+ and C terminals
	Use external regenerative resistor	Connect the regeneration resistance to terminals P+ and C, disconnect P+ and D, P0-25 = power value, P0-26 = resistance value
•	Vacant terminal	/
U/V/W/PE	Motor connection terminal	Connect to the motor

③ CN0 port [DS5L1]

Pin	Name
P-	Pulse input PUL-
P+24	Pulse input external power supply
D-	Direction input DIR-
D+24	Direction input external power supply
SI1	Input terminal 1
SI2	Input terminal 2
SI3	Input terminal 3
+24V	Input terminal +24V
SO1	Output terminal 1
SO2	Output terminal 2
SO3	Output terminal 3
COM	Output terminal ground

CN0 port [DS5C1/DS5N1]

Pin	Name
SI1	High speed input terminal 1
SI2	High speed input terminal 2
SI3	Normal input terminal 3
+24V	Input terminal +24V
SO1	Output terminal 1
SO2	Output terminal 2
SO3	Output terminal 3
COM	Output terminal ground

⑤ CN2 port [DS5L1/5C1/5N1]

Pin	Name
1	5V
2	GND
3	/
4	/
5	485-A
6	485-B

⑥ CN4 RS485 port [DS5L1]

Pin	Name
4	485-A
5	485-B
6	485-GND
Others	Reserved


⑦ Dial switch [DS5L1]

Switch1	Switch1	State
ON	ON	Pulse input differential 5V
OFF	OFF	Pulse input collector 24V

*Note: The directions of the two dialing codes must be consistent. If they are inconsistent, the pulse terminal of the driver will be burned once the power is supplied.

Terminal Definition

DS5C1 series 1.0~3kW



① RS-232 port

Pin	Name	Explanation
1	TXD	RS232 send
2	RXD	RS232 receive
3	GND	RS232 signal ground

④ CN0 port

Pin	Name
SI1	High speed input terminal 1
SI2	High speed input terminal 2
SI3	Normal input terminal 3
+24V	Input terminal +24V
SO1	Output terminal 1
SO2	Output terminal 2
SO3	Output terminal 3
COM	Output terminal ground

⑥ CN2□

Pin	Name
1	5V
2	GND
3	/
4	/
5	485-A
6	485-B

⑤ CN1 port

Pin	Name	Explanation
1	TX A+	TRANSMIT A+
2	TX A-	TRANSMIT A-
3	RX A+	RECEIVE A+
4	/	/
5	/	/
6	RX A-	RECEIVE A-
7	/	/
8	/	/
9	X B+	TRANSMIT B+
10	TX B-	TRANSMIT B-
11	RX B+	RECEIVE B+
12	/	/
13	/	/
14	RX B-	RECEIVE B-
15	/	/
16	/	/

② Main circuit terminal definition

DS5C1-21P0/21P5/22P3-PTA

Terminal	Function	Explanation
L1/L2/L3	Main circuit power supply input terminal	Single/three phase AC200~240V, 50/60Hz
P+/D/C	Use built-in regenerative resistor	Short connect P+ and D terminals, disconnect P+ and C
P+/D/C	Use external regenerative resistor	Connect the regeneration resistance to terminals P+ and C, disconnect P+ and D, P0-25 = power value, P0-26 = resistance value
P+/P-	Bus terminal	The real-time voltage of the bus can be measured. Please pay attention to the danger
U/V/W	Motor connection terminal	Connect to the motor <i>*Note:</i> The ground wire is on the heat sink. Please check it before power on.
⊕	Ground terminal	Connect with the motor grounding terminal for grounding


DS5C1-41P0/41P5/42P3/43P0-PTA

Terminal	Function	Explanation
R/S/T	Main circuit power supply input terminal	Three-phase AC380~440V, 50/60Hz
P+/D/C	Use built-in regenerative resistor	Short connect P+ and D terminals, disconnect P+ and C
P+/D/C	Use external regenerative resistor	Connect the regeneration resistance to terminals P+ and C, disconnect P+ and D, P0-25 = power value, P0-26 = resistance value
P+/P-	Bus terminal	The real-time voltage of the bus can be measured. Please pay attention to the danger
U/V/W	Motor connection terminal	Connect to the motor <i>*Note:</i> The ground wire is on the heat sink. Please check it before power on.
⊕	Ground terminal	Connect with the motor grounding terminal for grounding

③ Motor power terminal definition

Pin	Name
1	U
2	V
3	W
4	PE

DS5C1/DS5K1 series 11~15kW



① CN3 RS232 port DS5C1/DS5K1

Pin	Name	Explanation
1	TXD	RS232 send
2	RXD	RS232 receive
3	GND	RS232 signal ground

④ CN1 EtherCAT port DS5C1

Pin	Name	Explanation
1	TX A+	TRANSMIT A+
2	TX A-	TRANSMIT A-
3	RX A+	RECEIVE A+
4	/	/
5	/	/
6	RX A-	RECEIVE A-
7	/	/
8	/	/
9	X B+	TRANSMIT B+
10	TX B-	TRANSMIT B-
11	RX B+	RECEIVE B+
12	/	/
13	/	/
14	RX B-	RECEIVE B-
15	/	/
16	/	/

CN1 RS485 port

Pin	Name
4	485-A
5	485-B
6	485-GND
Others	Reserved

⑤ CN2 port

No.	Definition
1	Temperature-
2	Temperature+
3	485-B
4	485-A
5	PE
6	GND
7	GND
8	5V
9	5V

② Main circuit terminal definition DS5C1/DS5K1

Terminal	Function	Explanation
R/S/T	Main circuit power supply input terminal	Single phase AC200~240V, 50/60Hz
•	Vacant terminal	/
U/V/W	Motor connection terminal	Connect to the motor <i>*Note:</i> The ground wire is on the heat sink. Please check it before power on.
P+/PB	Use external regenerative resistor	Connect the regeneration resistance to terminals P+ and PB, P0-25 = power value, P0-26 = resistance value
P+/P-	Bus terminal	The real-time voltage of the bus can be measured. Please pay attention to the danger.
PE/PE	Ground terminal	Only the 11 and 15kW supported

③ CN0 port DS5C1/DS5K1

No.	Name	Explanation	No.	Name	Explanation
1	P-	Pulse-	11	+24V	Input common terminal
2	P+5	Pulse +5V	12	SI1	Input terminal
3	P+24	Pulse +24V	13	SI2	Input terminal
4	D-	Direction -	14	SI3	Input terminal
5	D+5	Direction +5V	15	SI4	Input terminal (high speed)
6	D+24	Direction +24V	16	SI5	Input terminal (high speed)
7	SO1+	Output terminal +	17	SO1-	Output terminal -
8	SO2+	Output terminal +	18	SO2-	Output terminal -
9	SO3+	Output terminal +	19	SO3-	Output terminal -
10	SO4+	Output terminal +	20	SO4-	Output terminal -

⑥ CN4 port DS5K1

No.	Name	Explanation	No.	Name	Explanation
1	VREF+	External speed analog differential input +	11	VREF-	External speed analog differential input -
2	TREF+	External torque analog differential input +	12	TREF-	External torque analog differential input -
3	GND	Analog input ground	13	GND	Analog input ground
4	OA+	Encoder frequency division output OA+	14	OA-	Encoder frequency division output OA-
5	OB+	Encoder frequency division output OB+	15	OB-	Encoder frequency division output OB-
6	OZ+	Encoder frequency division output OZ+	16	OZ-	Encoder frequency division output OZ-
7	OZ	Encoder frequency division output OZ	17	GND	Communication terminal ground
8	/	Vacant terminal	18	/	Vacant terminal
9	/	Vacant terminal	19	/	Vacant terminal
10	/	Vacant terminal	20	/	Vacant terminal

Terminal Definition

DS5C series

*This figure takes DS5C-20P4-PTA as an example.

DS5E series

*This figure takes DS5E-20P4-PTA as an example.

DS5L series

*This figure takes DS5L-20P4-PTA as an example.

DS5K series

*This figure takes DS5K-20P4-PTA as an example.

DS5F series

*This figure takes DS5F-20P4-PTA as an example.

DS5C series

① RS232 port

Pin	Name	Explanation
1	TXD	RS232 send
2	RXD	RS232 receive
3	GND	RS232 signal ground

② Main circuit terminal definition

Terminal	Function	Explanation
L/N R/S/T	Main circuit power supply input terminal	Single/three phase AC200~240V, 50/60Hz Three-phase AC380~440V, 50/60Hz
•	Vacant terminal	/
U/V/ W/PE	Motor connection terminal	Connect to the motor. Note: The ground wire is on the heat sink. Please check it before power on.
P+/D/C	Use built-in regenerative resistor	Short connect P+ and D terminals, disconnect P+ and C
	Use external regenerative resistor	Connect the regeneration resistance to terminals P+ and C, disconnect P+ and D. P0-25 = power value, P0-26 = resistance value

③ CN0 port

750W and below

Name	Explanation	Name	Explanation
P-	Pulse input PUL-	SI3	Input terminal 3
P+24V	Pulse input external power supply	+24V	Input terminal +24V
D-	Direction input DIR-	SO1	Output terminal 1
D+24V	Direction input external power supply	SO2	Output terminal 2
SI1	Input terminal 1	SO3	Output terminal 3
SI2	Input terminal 2	COM	Output terminal ground

1.5kW and up

Name	Explanation	Name	Explanation
P-	Pulse input PUL-	SI4	Input terminal 4
P+24V	Pulse input external power supply	+24V	Input terminal +24V
D-	Direction input DIR-	SO1	Output terminal 1
D+24V	Direction input external power supply	SO2	Output terminal 2
SI1	Input terminal 1	SO3	Output terminal 3
SI2	Input terminal 2	SO4	Output terminal 4
SI3	Input terminal 3	COM	Output terminal ground

④ CN1 port

Pin	Name	Explanation	Pin	Name	Explanation
1	TX A+	TRANSMIT A+	9	TX B+	TRANSMIT B+
2	TX A-	TRANSMIT A-	10	TX B-	TRANSMIT B-
3	RX A+	RECEIVE A+	11	RX B+	RECEIVE B+
4	/	/	12	/	/
5	/	/	13	/	/
6	RX A-	RECEIVE A-	14	RX B-	RECEIVE B-
7	/	/	15	/	/
8	/	/	16	/	/

⑤ CN2 port

Pin	Name
1	5V
2	GND
3	/
4	/
5	485-A
6	485-B

Terminal definition

DS5E series

③ CN0 port

750W and below

Name	Explanation	Name	Explanation
P-	Pulse input PUL-	SI3	Input terminal 3
P+24V	Pulse input external power supply	+24V	Input terminal +24V
D-	Direction input DIR-	SO1	Output terminal 1
D+24V	Direction input external power supply	SO2	Output terminal 2
SI1	Input terminal 1	SO3	Output terminal 3
SI2	Input terminal 2	COM	Output terminal ground

1.5kW and up

Name	Explanation	Name	Explanation
P-	Pulse input PUL-	SI4	Input terminal 4
P+24V	Pulse input external power supply	+24V	Input terminal +24V
D-	Direction input DIR-	SO1	Output terminal 1
D+24V	Direction input external power supply	SO2	Output terminal 2
SI1	Input terminal 1	SO3	Output terminal 3
SI2	Input terminal 2	SO4	Output terminal 4
SI3	Input terminal 3	COM	Output terminal ground

④ CN1 port

Pin	Name	Explanation
1	GND	GND-485
2	A1	RS485+
3	B1	RS485-
4	A2	RS485+
5	B2	RS485-
6	GND	GND-485
7	NC	Reserved
8		
9		

⑤ CN2 port

Pin	Name
1	5V
2	GND
3	/
4	/
5	485-A
6	485-B

DS5L series

③ CN0 port

750W and below

Name	Explanation	Name	Explanation
P-	Pulse input PUL-	SI3	Input terminal 3
P+24V	Pulse input external power supply	+24V	Input terminal +24V
D-	Direction input DIR-	SO1	Output terminal 1
D+24V	Direction input external power supply	SO2	Output terminal 2
SI1	Input terminal 1	SO3	Output terminal 3
SI2	Input terminal 2	COM	Output terminal ground

1.5kW and up

Name	Explanation	Name	Explanation
P-	Pulse input PUL-	SI4	Input terminal 4
P+24V	Pulse input external power supply	+24V	Input terminal +24V
D-	Direction input DIR-	SO1	Output terminal 1
D+24V	Direction input external power supply	SO2	Output terminal 2
SI1	Input terminal 1	SO3	Output terminal 3
SI2	Input terminal 2	SO4	Output terminal 4
SI3	Input terminal 3	COM	Output terminal ground

④ CN1 port

Pin	Name	Explanation
1	NC	Reserved
2		
3		
4		
5		
6		
7		
8		
9		

⑤ CN2 port

Pin	Name
1	5V
2	GND
3	/
4	/
5	485-A
6	485-B

DS5K series

③ CN0 port

Pin	Name	Explanation	Pin	Name	Explanation	
1	P-	Pulse input PUL-	23	SI4	Input terminal	
2	P+5	Pulse input external power supply +5V	24	NC	Vacant terminal	
3	P+24	Pulse input external power supply +24V	25			
			26			
4	D-	Direction input DIR-	27			
5	D+5	Direction input external power supply +5V	28	SI5	High speed input terminal	
			29			
6	D+24	Direction input external power supply +24V	30	+24V	Input terminal +24V	
7	SO1	Output terminal	31	NC	Vacant terminal	
8	SO2		32			
9	SO3		33			
10	SO4		34			
11	NC	Vacant terminal	35	OA+	Encoder frequency division output OA+	
12			36	OA-	Encoder frequency division output OA-	
13				37	OB+	Encoder frequency division output OB+
14					OB-	Encoder frequency division output OB-
15	COM	Output terminal ground	38	OB-	Encoder frequency division output OB-	
16	485+	Communication terminal +	39	OZ+	Encoder frequency division output OZ+	
17	485-	Communication terminal -	40	OZ-	Encoder frequency division output OZ-	
18	GND	Communication terminal ground	41	NC	Vacant terminal	
19	NC	Vacant terminal	42			
20	SI1	Input terminal	43			
21	SI2		44			
22	SI3					

④ CN1 port (no function)

⑤ CN2 port

Pin	Name
1	5V
2	GND
3	/
4	/
5	485-A
6	485-B

DS5F series

③ CN0 port

Pin	Name	Explanation	Pin	Name	Explanation
1	P-	Pulse input PUL-	27	SI8	Input terminal
2	P+5	Pulse input external power supply +5V	28	SI9	
3	P+24	Pulse input external power supply +24V	29	SI10	High speed input terminal
4	D-	Direction input DIR-	30	+24V	Input terminal +24V
5	D+5	Direction input external power supply +5V	31	T-REF+	External torque analog differential input +
6	D+24	Direction input external power supply +24V	32	T-REF-	External torque analog differential input +
7	SO1	Output terminal	33	V-REF+	External torque analog differential input +
8	SO2		34	V-REF-	External torque analog differential input +
9	SO3		35	OA+	Encoder frequency division output OA+
10	SO4		36	OA-	Encoder frequency division output OA-
11	SO5		37	OB+	Encoder frequency division output OB+
12	SO6		38	OB-	Encoder frequency division output OB-
13	SO7		39	OZ+	Encoder frequency division output OZ+
14	SO8		40	OZ-	Encoder frequency division output OZ-
15	COM	Output terminal ground	41	HPUL+	Line driver high speed pulse +
16	485+	Communication terminal +	42	HPUL-	Line driver high speed pulse -
17	485-	Communication terminal -	43	HDIR+	Line driver high speed direction +
18	GND	Communication terminal ground	44	HDIR-	Line driver high speed direction -
19	GND	Analog input ground			
20	SI1	Input terminal			
21	SI2				
22	SI3				
23	SI4				
24	SI5				
25	SI6				
26	SI7				

④ CN1 port

Pin Name		Explanation	Pin Name		Explanation
1	Z-	Full closed loop input Z-	9	Z+	Full closed loop input Z+
2	B-	Full closed loop input B-	10	/	Vacant terminal
3	B+	Full closed loop input B+	11		
4	A+	Full closed loop input A+	12		
5	A-	Full closed loop input A-	13		
6	GND	Grating ruler power supply GND	14		
7	GND		15		
8	5V	Grating ruler power supply 5V			

⑤ CN2 port

Pin	Name
1	5V
2	GND
3	/
4	/
5	485-A
6	485-B


Drive Specification

Specification		Model	Pulse type		EtherCAT bus type		CANopen bus type	X-NET bus type	Full function type	Standard type	
		DS5L1 series	DS5L series	DS5C1 series	DS5C series	DS5N1 series	DS5E series	DS5F series	DS5K1 series	DS5K series	
Basic specification	Power range (kW)		0.1~0.75	0.1~2.6	0.1~15	0.1~32	0.1~0.75	0.1~22	0.1~7.5	11~15	0.1~3.0
	Input power supply		Single/three phase AC200~240V, 50/60Hz. Three-phase AC380V~440V, 50/60Hz								
	Encoder feedback		17-bit/23-bit communication encoder								
	Control mode		Three-phase full wave rectifier IPM, PWM control, sine wave current drive mode								
	Use environment	Ambient temperature	Operation: -10℃~40℃ (no condensation)/storage: -20℃~60℃ (no condensation)								
		Ambient humidity	Operation/storage: 90%RH and below (no condensation)								
		Vibration/shock resistance	4.9m/s ² / 19.6m/s ²								
	Function	Electronic CAM	No								
		Protection function	Overvoltage, undervoltage, overheating, overcurrent, overload, overspeed, analog input abnormality, excessive position deviation, output short circuit, encoder abnormality, regeneration abnormality protection, overtravel protection, oscillation protection, phase loss protection, etc								
		Dynamic brake	No								
		Communication function	RS232: standard ModbusRTU protocol RS485: standard ModbusRTU protocol	RS232: standard ModbusRTU protocol	RS232: standard ModbusRTU protocol EtherCAT: support EtherCAT bus communication (max 32 axes)		RS232: standard ModbusRTU protocol CANopen: support CANopen bus communication (max 64 axes)	RS232: standard ModbusRTU protocol RS485: standard ModbusRTU protocol Support X-NET bus communication (max 20 axes)	RS232: standard ModbusRTU protocol RS485: standard ModbusRTU protocol		
		Brake resistor	Built-in brake resistor, external brake resistor can be connected								
		Display and operate	5-bit LED indicator light, power indicator light, 4 buttons								
	Position output	Output form	No							ABZ differential feedback output	
		Frequency division function	No							Yes	
		Collector Z phase output	Yes								
Analog input		No							2 channels input	No	
I/O signal	Digital input (SI)		3 channels	3 channels (750W and below) 4 channels (above 750W)	3 channels	3 channels (750W and below) 4 channels (above 750W)	3 channels	3 channels (750W and below) 4 channels (above 750W)	10 channels	5 channels	
			Servo enable, alarm clear, no forward rotation, no reverse rotation, torque limit selection, internal speed selection, gear ratio switching, mode switching, pulse input prohibition, zero speed locking, position deviation clear, internal position step change signal, internal control mode direction switching								
	Digital output (SO)		3 channels	3 channels (750W and below) 4 channels (above 750W)	3 channels	3 channels (750W and below) 4 channels (above 750W)	3 channels	3 channels (750W and below) 4 channels (above 750W)	8 channels	4 channels	
Positioning completion, servo ready, alarm output, torque limit output, same speed detection, rotation detection, speed arrival, brake release output and warning output											
Position control mode	Max input pulse frequency		Collector open: 200kpps (5C1/5N1 not support pulse)						Collector open: 200kpps [Optocoupler] Differential input: 500kpps [Optocoupler] Long line reception: 2Mpps [only DS5F series support]		
	Pulse command mode		3.3V~5V/18~24V pulse+direction, AB phase pulse, CW/CCW signal	18~24V pulse+direction, AB phase pulse, CW/CCW signal (5C cannot support CW/CCW, 5C1/5N1 not support external pulse)					3.3V~5V/18~24V pulse+direction, AB phase pulse, CW/CCW signal		
	Control mode		External pulse/built-in position		Built-in position/EtherCAT motion bus	External pulse/built-in position/EtherCAT motion bus	Built-in position/CANopen motion bus	External pulse/built-in position/X-NET motion bus	External pulse/built-in position		
	Feedforward compensation		0~100% (set the resolution to 1%)								
	Positioning complete width		1~65535 command unit (set the resolution to 1 command unit)								
	Electronic gear ratio		1/10000±B/A≤10000								
Speed control mode	Control mode		Analog speed control (only DS5F support), internal three segments of speed, external speed mode								
	Command smoothing mode		Low pass filter, smooth filter								
	Analog input	Voltage range	No						-10V~+10V (resolution 12-bit)		No
	Input impedance		No						72KΩ		No
	Torque limit		Internal parameter						Internal parameter/external analog		Internal parameter
Torque control mode	Speed change rate		External load rated change 0~100%: below ±0.01% (at rated speed)								
			Rated voltage ±10%: 0.01% (at rated speed)								
			Ambient temperature 20±25℃: below ±0.01% (at rated speed)								
	Control mode		Analog speed control (only DS5F support), internal torque								
	Analog input	Voltage range	No						-10V~+10V (resolution 12-bit)		No
Input impedance		No						72KΩ		No	
Speed limit		Internal parameter						Internal parameter/external analog		Internal parameter	
Bus control mode	Control axis number		No	32 axes		64 axes		20 axes		No	
	Communication protocol		No	EtherCAT protocol		CANopen protocol		X-NET protocol		No	


Drive Dimension Diagram

(Unit: mm)


DS5L1-20P1/2/4-PTA




DS5C1/DS5N1-20P1/2/4-PTA




DS5L1-20P7-PTA




DS5C1/DS5N1-20P7-PTA




DS5C1-21P0/41P0/41P5-PTA




DS5C1-21P5/22P3/42P3/43P0-PTA



DS5C1-411P0/415P0-PTA




DS5K1-411P0/415P0-PTA




Drive dimension diagram

(Unit: mm)


DS5E-20P1/20P2/20P4-PTA DS5F-20P1/20P2/20P4-PTA DS5E-20P7-PTA DS5C-20P7-PTA DS5K-20P7-PTA
DS5L-20P1/20P2/20P4-PTA DS5K-20P1/20P2/20P4-PTA DS5L-20P7-PTA DS5F-20P7-PTA
DS5C-20P1/20P2/20P4-PTA



DS5E-21P0/21P5/22P3/22P6/41P0-PTA DS5E-43P0-PTA-H DS5C-43P0-PTA-H
DS5L-21P0/21P5/22P3/22P6-PTA DS5K-43P0-PTA-H DS5F-43P0-PTA-H
DS5C-21P0/21P5/22P3/22P6/41P0/41P5-PTA
DS5F-21P0/21P5/22P3/22P6-PTA
DS5K-21P0/21P5/22P3/22P6/41P5-PTA




DS5E-45P5/47P5-PTA-H DS5C-45P5/47P5-PTA-H DS5E-411P0/415P0-PTA DS5C-411P0/415P0-PTA
DS5F-45P5/47P5-PTA-H



*注: 增强型伺服与非增强型伺服尺寸一致。

DS5C-422P0-PTA DS5C-432P0-PTA



MS series motor parameters

MS6 series

Voltage level		AC 220V															
Motor model		MS6H-40		MS6H-60		MS6S-60		MS6H-60		MS6S-80		MS6H-80		MS6S-80	MS6H-80	MS6S-80	MS6H-80
		CS/CM30B(Z)1/2	CS/CM/TL30B(Z)3	CS/CM30B(Z)1/2	CS/CM/TL30B(Z)3	CS/CM30B(Z)1/2	CS/CM/TL30B3	CS/CM30B(Z)1/2	CS/CM/TL30B3	CS/CM30B(Z)1/2	CS/CM/TL30B(Z)3	CS/CM30B(Z)1/2	CS/CM/TL30B(Z)3	CS/CM20B(Z)1/2	CS/CM20B(Z)1/2	CS/CM30B(Z)3	CS/CM30B(Z)3
		20P1	20P2	20P4	20P4	20P7	20P7	20P7	20P7	20P7	20P7	20P7	20P7	20P7	21P0	21P0	21P0
Rated power (kW)		0.1	0.2	0.4	0.4	0.4	0.4	0.75	0.75	0.75	0.75	0.75	1				
Rated speed (rpm)		3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	2000	3000				
Max speed (rpm)		6500	6500	6500	6500	6000	6000	5200	5200	5200	5200	3500	4000				
Rated torque (N·m)		0.32	0.64	1.27	1.27	1.27	1.27	2.39	2.39	2.39	2.39	3.5	3.18				
Max torque (N·m)		0.96	2.24	4.45	4.45	4.45	4.45	7.17	7.17	7.17	7.17	10.5	9.54				
Rated current (mA)		850	950	1800	1900	2700	2600	2800	4000	4100	4100	4100	4100				
Rotor inertia (10 ⁻⁴ ·kg·m ²)		86(93)	70	277(295)	271(275)	273(262)	285	520(590)	520	980(1030)	980	1670(1691)	1550	1208(1261)	2445(2553)	1182	2391
Inertia type		High inertia		High inertia		Low inertia		High inertia		Low inertia		High inertia		Low inertia	High inertia	Low inertia	High inertia
Recommended rotor inertia ratio		30															
Electrical constant τe(ms)		0.702	1.04	1.91	1.64	2.95	2.96	2.09	1.63	5.184	5.53	4.567	4.58	5.55	4.865	5.89	4.97
Mechanical constant τm(ms)		1.635(1.768)	1.26	1.74(1.86)	1.26(1.28)	0.603(0.623)	0.57	0.929(1.054)	0.93	0.705(0.741)	0.69	0.925(0.937)	1	0.55(0.574)	0.55(0.574)	0.53	0.93
EMF constant Ke (mV/rpm)		38	33	24.03	31.25	44	44.25	49	43.98	56	55	54	56	120	115.5	75	73
Torque constant Kt (Nm/A)		0.376	0.34	0.36	0.34	0.47	0.47	0.47	0.45	0.598	0.58	0.598	0.58	0.875		0.78	
Pole of pairs		5															
Encoder bit		17	17/23	17	17/23	17	17/23	17	17/23	17	17/23	17	17/23	17	17/23	17	17/23
Encoder type		magnetism	magnetism (photoelectricity)	magnetism	magnetism (photoelectricity)	magnetism	magnetism (photoelectricity)	magnetism	magnetism (photoelectricity)	magnetism	magnetism (photoelectricity)	magnetism	magnetism (photoelectricity)	magnetism	magnetism (photoelectricity)	magnetism	magnetism (photoelectricity)
Motor insulation grade		ClassF(155°C)															
Protection level		Ip65	Ip67	Ip66	Ip67	Ip66	Ip67	Ip66	Ip67	Ip66	Ip67	Ip66	Ip67		Ip66		Ip67
Use environment	Ambient temperature	-15°C~+40°C (no freezing)															
	Ambient humidity	Relative humidity <90% (no condensation)															

Voltage level		AC 220V						AC 380V						AC 220V					
Motor model		MS6S-100		MS6H-130										CS/CM20B2		TL20B2		CS/CM20B2Z	
		CS/CM30B2	CS/CM15B2	CS/CM15B2Z	TL15B2	TL15B2Z	CS/CM15B2	CS/CM15B2Z	TL15B2	TL15B2Z	CS/CM15B2	CS/CM15B2Z	TL15B2						
21P5		20P8	20P8		40P8		40P8		41P3		41P3		21P5		21P5				
Rated power (kW)		1.5	0.85	0.85		0.85		0.85		1.3		1.3		1.5		1.5			
Rated speed (rpm)		3000	1500	1500		1500		1500		1500		1500		2000		2000			
Max speed (rpm)		4500	3000	3000		3000		3000		3000		3000		3000		3000			
Rated torque (N·m)		4.8	5.41	5.41		5.41		5.41		8.3		8.3		7.16		7.16			
Max torque (N·m)		12	16.23	16.23		16.23		16.23		24.9		24.9		18		18			
Rated current (mA)		8000	6000	6000		3500		3500		6000		6000		8000		8000			
Rotor inertia (10 ⁻⁴ ·7kg·m ²)		2812	13860	15340	13860	15340	13860	15340	13860	15340	20000	21440	20000	21440	20000	21440			
Inertia type		Low inertia	High inertia		High inertia		High inertia		High inertia		High inertia		High inertia		High inertia				
Recommended rotor inertia ratio		15	10		10		10		10		10		10		10				
Electrical constant τ_e (ms)		10.791	6.944		6.944		6.722		6.722		9.229		9.229		8.409				
Mechanical constant τ_m (ms)		0.61	1.823	2.017	1.823	2.017	1.844	2.041	1.844	2.041	1.496	1.603	1.496	1.603	1.523	1.633			
EMF constant K_e (mV/rpm)		57	89		89		149		149		127		127		86				
Torque constant K_t (Nm/A)		0.6	0.902		0.902		1.546		1.546		1.383		1.383		0.895				
Pole of pairs		5																	
Encoder bit		17	23	17	23		17		23		17		23		17	23			
Encoder type		magnetism	photoelectricity	magnetism	photoelectricity		magnetism		photoelectricity		magnetism		photoelectricity		magnetism	photoelectricity			
Motor insulation grade		ClassF(155°C)																	
Protection level		Ip65																	
Use environ-ment	Ambient temperature	-15°C~+40°C (no freezing)																	
	Ambient humidity	Relative humidity <90% (no condensation)																	

Voltage level		AC 220V								AC 380V																	
Motor model		TL20B2Z		CS/CM15B2Z		TL15B2		TL15B2Z		CS/CM15B2Z		TL15B2		TL15B2Z		CS/CM15B2Z		TL15B2		TL15B2Z		CS/CM15B2Z		TL15B2		TL15B2Z	
		21P5	21P8	21P8	21P8	21P8	21P8	22P3	22P3	41P8	41P8	42P3	42P3														
Rated power (kW)		1.5	1.8	1.8	2.3	2.3	1.8	1.8	2.3	2.3	1.8	1.8	2.3	2.3													
Rated speed (rpm)		2000	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500													
Max speed (rpm)		3000	2500	2500	2500	2500	2500	3000	3000	3000	3000	3000	3000	3000													
Rated torque (N·m)		7.16	11.5	11.5	14.6	14.6	11.5	11.5	11.5	11.5	14.6	14.6	14.6	14.6													
Max torque (N·m)		18	34.5	34.5	36.5	36.5	28.75	28.75	28.75	28.75	36.5	36.5	36.5	36.5													
Rated current (mA)		8000	10000	10000	11800	11800	7400	7400	7400	7400	8500	8500	8500	8500													
Rotor inertia (10 ⁻⁴ ·kg·m ²)		21440	28500	29940	28500	29940	35240	36260	35240	36260	28500	29940	28500	29940	35240	36260	35240	36260									
Inertia type		High inertia	High inertia	High inertia	High inertia	High inertia	High inertia	High inertia	High inertia	High inertia	High inertia	High inertia	High inertia	High inertia													
Recommended rotor inertia ratio		10	10	10	10	10	10	10	10	10	10	10	10	10													
Electrical constant τ_e (ms)		8.409	8.37	8.37	9.893	9.893	9.893	9.893	9.973	9.973	9.887	9.887	9.887	9.887													
Mechanical constant τ_m (ms)		1.633	1.414	1.486	1.414	1.486	1.234	1.27	1.234	1.27	1.252	1.316	1.252	1.316	1.249	1.285	1.249	1.285									
EMF constant K_e (mV/rpm)		86	106	106	115	115	115	144	144	144	155	155	155	155													
Torque constant K_t (Nm/A)		0.895	1.15	1.15	1.237	1.237	1.237	1.554	1.554	1.554	1.718	1.718	1.718	1.718													
Pole of pairs		5																									
Encoder bit		23	17	23	17	23	17	23	17	23	17	23	17	23													
Encoder type		photoelectricity	magnetism	photoelectricity	magnetism	photoelectricity	magnetism	photoelectricity	magnetism	photoelectricity	magnetism	photoelectricity	magnetism	photoelectricity													
Motor insulation grade		ClassF(155°C)																									
Protection level		Ip65																									
Use environ-ment	Ambient temperature	-15°C~+40°C (no freezing)																									
	Ambient humidity	Relative humidity <90% (no condensation)																									

MS Series Motor Parameters

MS6 series

Voltage level		AC 380V																
Motor model		MS6H-130				MS6H-180												
		TL15BZ2	CS/CM15B2	CS/CM15BZ2	TL15B2	TL15BZ2	CS/CM15B2	CS/CM15BZ2	TL15B2	TL15BZ2	CS/CM15B2	CS/CM15BZ2	TL15B2	TL15BZ2	CS/CM15B2	CS/CM15BZ2	TL15B2	TL15BZ2
Rated power (kW)		42P3	43P0		43P0		44P4		44P4		45P5		45P5		47P5		47P5	
Rated speed (rpm)		2.3	3		3		4.4		4.4		5.5		5.5		7.5		7.5	
Max speed (rpm)		1500	1500		1500		1500		1500		1500		1500		1500		1500	
Rated torque (N·m)		3000	3000		3000		3000		3000		3000		3000		3000		3000	
Rated torque (N·m)		14.6	19		19		28		28		35		35		48		48	
Max torque (N·m)		36.5	51.3		51.3		84		84		87.5		87.5		120		120	
Rated current (mA)		8500	11000		11000	29700	16500		16500		19700		19700		25000		25000	
Rotor inertia (10 ⁻⁴ ·7kg·m ²)		36260	51000	55490	51000	55490	73280	78040	73280	78040	90250	95200	90250	95200	132000	134690	132000	134690
Inertia type		High inertia	High inertia		High inertia		High inertia		High inertia		High inertia		High inertia		High inertia		High inertia	
Recommended rotor inertia ratio		10	10		10		10		10		10		10		10		10	
Electrical constant τ _e (ms)		9.887	22.539		22.539		25.547		25.547		26.195		26.195		25.176		25.176	
Mechanical constant τ _m (ms)		1.285	1.251	1.361	1.251	1.361	1.023	1.09	1.023	1.09	0.957	1.01	0.957	1.01	0.907	0.925	0.907	0.925
EMF constant K _e (mV/rpm)		155	160		160		160		160		160		160		172		172	
Torque constant K _t (Nm/A)		1.718	1.727		1.727		1.636		1.636		1.777		1.777		1.92		1.92	
Pole of pairs		5																
Encoder bit		23	17		23		17/23		17/23		17/23		17/23		17/23		17/23	
Encoder type		photoelectricity	magnetism		photoelectricity		magnetism (photoelectricity)		magnetism (photoelectricity)		magnetism (photoelectricity)		magnetism (photoelectricity)		magnetism (photoelectricity)		magnetism (photoelectricity)	
Motor insulation grade		ClassF(155°C)																
Protection level		Ip65																
Use environ-ment	Ambient temperature	-15°C--+40°C (no freezing)																
	Ambient humidity	Relative humidity <90% (no condensation)																

MS5 series

Voltage level		AC 220V											
Motor model		MS5S-110STE						MS5G-130STE					
		CS/CM00320B 21P0-S01	TL03230B□ 21P0-S01	CS/CM04830B□ 21P5-S01	TL04830B□ 21P5-S01	CS/CM06030B□ 21P8-S01	TL06030B□ 21P8-S01	CS/CM05415B 20P8-S01	CS/CM05415BZ 20P8-S01	TL05415B 20P8-S01	TL05415BZ 20P8-S01	CS/CM06025B 21P5-S01	CS/CM06025BZ 21P5-S01
Rated power (kW)		1	1	1.5	1.5	1.8	1.8	0.85	0.85	0.85	0.85	1.5	1.5
Rated speed (rpm)		3000	3000	2000	2000	3000	3000	1500	1500	1500	1500	2500	2500
Max speed (rpm)		6000	6000	4500	4500	4500	4500	2000	2000	2000	2000	3000	3000
Rated torque (N·m)		3.18	3.18	4.77	4.77	6	6	5.41	5.41	5.41	5.41	6	6
Max torque (N·m)		7.95	7.95	9.54	9.54	12	12	15.15	15.15	15.15	15.15	15	15
Rated current (mA)		7500	7500	7500	7500	9500	7500	4200	4200	4200	4200	7500	7500
Rotor inertia (10 ⁻⁴ ·7kg·m ²)		2869	2869	3360	3360	4170	4170	8480	9717	8480	9717	9440	9440
Inertia type		Low inertia	Low inertia	Low inertia	Low inertia	Low inertia	Low inertia	Medium inertia	Medium inertia	Medium inertia	Medium inertia	Medium inertia	Medium inertia
Recommended rotor inertia ratio		15	15	15	15	10	10	10	10	10	10	10	10
Electrical constant τ _e (ms)		18.363	18.363	20.606	20.606	20.863	20.863	7.79	7.79	7.79	7.79	9.368	9.368
Mechanical constant τ _m (ms)		0.984	0.984	0.727	0.727	0.583	0.583	1.293	1.482	1.293	1.482	1.113	1.32
EMF constant K _e (mV/rpm)		51	51	64	64	62	62	123	123	123	123	76	76
Torque constant K _t (Nm/A)		0.424	0.424	0.636	0.636	0.632	0.632	1.286	1.286	1.286	1.286	0.8	0.8
Pole of pairs		5											
Encoder bit		17	23	17	23	17	23	17	17	23	23	17	17
Encoder type		magnetism	photoelectricity	magnetism	photoelectricity	magnetism	photoelectricity	magnetism	magnetism	photoelectricity	photoelectricity	magnetism	magnetism
Motor insulation grade		ClassF(155°C)											
Protection level		Ip65											
Use environ- ment	Ambient temperature	-15°C~+40°C (no freezing)											
	Ambient humidity	Relative humidity <90% (no condensation)											

Voltage level		AC 220V					AC 380V					AC 220V	
Motor model		MS5G-130STE											
		CS/CM10015B 21P5-S01	CS/CM10015BZ 21P5-S01	CS07220B 21P5-S01	CS07220BZ 21P5-S01	TL07220B 21P5-S01	TL07220BZ 41P5-S01	CS/CM07220B 41P5-S01	CS/CM07220BZ 41P5-S01	TL07220B 41P5-S01	TL07220BZ 41P5-S01	CS/CM11515B 21P8-S01	CS/CM11515BZ 21P8-S01
Rated power (kW)		1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.8	1.8
Rated speed (rpm)		1500	1500	2000	2000	2000	2000	2000	2000	2000	2000	1500	1500
Max speed (rpm)		2500	2500	3000	3000	3000	3000	3000	3000	3000	3000	2000	2000
Rated torque (N·m)		10	10	7.16	7.16	7.16	7.16	7.16	7.16	7.16	7.16	11.5	11.5
Max torque (N·m)		25	25	17.9	17.9	17.9	17.9	25.06	25.06	25.06	25.06	23	23
Rated current (mA)		7500	7500	7500	7500	7500	7500	5000	5000	5000	5000	9000	9000
Rotor inertia (10 ⁻⁴ ·Kg·m ²)		14400	14400	11780	13130	11780	13130	11780	13130	11780	13130	17710	19060
Inertia type		Medium inertia											
Recommended rotor inertia ratio		10	10	10	10	10	10	10	10	10	10	10	10
Electrical constant τ _e (ms)		10.084	10.084	8.292	8.292	8.292	8.292	9.874	9.874	9.874	9.874	9.142	9.142
Mechanical constant τ _m (ms)		0.847	0.847	1.076	1.199	1.076	1.199	0.925	1.031	0.925	1.031	1.113	0.918
EMF constant K _e (mV/rpm)		122	122	88	88	88	88	132	132	132	132	116	116
Torque constant K _t (Nm/A)		1.333	1.333	0.955	0.955	0.955	0.955	1.432	1.432	1.432	1.432	1.278	1.278
Pole of pairs		5											
Encoder bit		17	17	17	17	23	23	17	17	23	23	17	17
Encoder type		magnetism	magnetism	magnetism	magnetism	photoelectricity	photoelectricity	magnetism	magnetism	photoelectricity	photoelectricity	magnetism	magnetism
Motor insulation grade		ClassF(155°C)											
Protection level		Ip65											
Use environ-ment	Ambient temperature	-15°C~+40°C (no freezing)											
	Ambient humidity	Relative humidity <90% (no condensation)											

MS5 / MS series

Voltage level		AC 220V		AC 380V				AC 220V				AC 380V	
Motor model		MS5G-130STE											
		TL11515B 21P8-S01	TL11515BZ 21P8-S01	CS/CM11515B 41P8-S01	TL11515B 41P8-S01	CS/CM11515BZ 41P8-S01	TL11515BZ 22P3-S01	CS/CM14615B 22P3-S01	CS/CM14615BZ 22P3-S01	TL14615B 22P3-S01	TL14615BZ 22P3-S01	CS/CM14615B 42P3-S01	TL14615B 42P3-S01
Rated power (kW)		1.8	1.8	1.8	1.8	1.8	1.8	2.3	2.3	2.3	2.3	2.3	2.3
Rated speed (rpm)		1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Max speed (rpm)		2000	2000	3000	3000	3000	3000	2000	2000	2000	2000	3000	3000
Rated torque (N·m)		11.5	11.5	11.5	11.5	11.5	11.5	14.6	14.6	14.6	14.6	14.6	14.6
Max torque (N·m)		23	23	28.75	28.75	28.75	28.75	29.2	29.2	29.2	29.2	36.5	36.5
Rated current (mA)		9000	9000	6800	6800	6800	6800	9000	9000	9000	9000	8500	8500
Rotor inertia (10 ⁻⁴ ·7kg·m ²)		17710	19060	17710	17710	18974	18974	22324	23560	22324	23560	22320	22320
Inertia type		Medium inertia											
Recommended rotor inertia ratio		10	10	10	10	10	10	10	10	10	10	10	10
Electrical constant τ _e (ms)		9.142	9.142	10.588	10.588	10.588	10.588	9.394	9.394	9.394	9.394	9.886	9.886
Mechanical constant τ _m (ms)		0.853	0.918	0.762	0.751	0.816	0.816	0.815	0.86	0.815	0.86	0.774	0.774
EMF constant Ke (mV/rpm)		116	116	155.54	155.54	155.54	155.54	148.536	148.536	148.536	148.536	156.487	156.487
Torque constant Kt (Nm/A)		1.278	1.278	1.691	1.716	1.691	1.691	1.622	1.622	1.622	1.622	1.718	1.718
Pole of pairs		5											
Encoder bit		23	23	17	23	17	23	17	17	23	23	17	23
Encoder type		photoelectricity	photoelectricity	magnetism	photoelectricity	magnetism	photoelectricity	magnetism	magnetism	photoelectricity	photoelectricity	magnetism	photoelectricity
Motor insulation grade		ClassF(155°C)											
Protection level		Ip65											
Use environ-ment	Ambient temperature	-15°C~-+40°C (no freezing)											
	Ambient humidity	Relative humidity <90% (no condensation)											

Brake Specification

Motor	MS series				MS5 series								MS6 series					
	110 flange 04/05	130 flange 06/07	130 flange 10/15	220 flange	40 flange	60 flange	80 flange	110 flange	130 flange	180 flange 19/27	180 flange 35/48	40 flange	60 flange	80 flange	100 flange	130 flange	180 flange	
Brake parameter																		
Static friction torque(N·m)	≥8	≥8	≥15	≥115	≥0.3	≥1.3	≥3.2	≥8	≥15	≥30	≥50	≥0.32	≥1.3	≥2.5	≥8	≥15	≥58	
Rated power(W)	14.4	14.4	25	55	6	7.2	11.5	14.4	25	31	51	6.1	7.2	8	17.6	25	30	
Attraction time(ms)	<80	<80	<100	<200	<50	<50	<60	<80	<100	<110	<110	<35	<50	<80	<100	<100	<180	
Release time(ms)	<40	<40	<60	<80	<20	<20	<40	<40	<60	<80	<80	<20	<20	<40	<50	<60	<80	
Excitation current DC(A)	0.6	0.6	1	2.3	0.25	0.3	0.47	0.6	1	1.3	2.1	0.25	0.3	0.233	0.73	1	1.25	
Attraction voltage DC(V)	<16.8	<16.8	<16.8	<19.2	<16.8	<16.8	<16.8	<16.8	<16.8	<18	<19	<16.8	<18	<16.8	<16.8	<16.8	<16.8	
Release voltage DC(V)	>1.5	>1.5	>1.5	>1.5	>0.5	>1.5	>1.5	>1.5	>1.5	>4	>5	>1.5	>1.5	>1	>1	>1.5	>1.5	
Excitation voltage DC(V)	DC24±10%																	


*Note: 04/05 below flange indicates the motor torque.

MS Motor Axial and Radial Force Specification


Base number (mm)	40 flange	60 flange	80 flange	100 flange	110 flange	130 flange	180 flange	220 flange
Axial force (N)	57	74	147	≤200	250	300	400	≤500
Radial force (N)	78	245	392	500	500	600	800	1000

MS6 Series T/N Curve


MS6H-40CS/CM30B3-20P1




MS6S-80CS/CM30B3-21P0




MS6S-60CS/CM30B(Z)□-20P4




MS6S-60CS/CM30B3-20P4




MS6H-80CS/CM30B3-21P0




MS6H-80CS/CM30B(Z)□-20P7




MS6H-60CS/CM30B3-20P4




MS6H-40CS/CM30B1-20P1
MS6H-40CS/CM30BZ1-20P1




MS6S-80CS/CM30B(Z)□-20P7
MS6S-80CS/CM30B(Z)□-20P7




MS6S-80CS/CM30B3-20P7




MS6H-60CS/CM30B1-20P2
MS6H-60CS/CM30BZ1-20P2




MS6H-80CS/CM20B□-20P7




MS6H-80CS/CM30B3-20P7



MS6H-60CS/CM30B(Z)□-20P4




MS6S-80CS/CM20B(Z)□-20P7




MS6 Series T/N Curve


MS6H-130CS/CM15B(Z)2-20P8
MS6H-130TL15B(Z)2-20P8




MS6H-130CS/CM15B(Z)2-21P8
MS6H-130TL15B(Z)2-21P8




MS6H-180CS/CM15B2-44P4
MS6H-180TL15B2-44P4




MS6H-130CS/CM15B(Z)2-40P8
MS6H-130TL15B(Z)2-40P8




MS6H-130CS15B(Z)2-41P8
MS6H-130TL15B(Z)2-41P8




MS6H-180CS/CM15B(Z)2-45P5
MS6H-180TL15B(Z)2-45P5




MS6H-130CS/CM15B(Z)2-41P3
MS6H-130TL15B(Z)2-41P3




MS6H-130CS/CM15B(Z)2-22P3
MS6H-130TL15B(Z)2-22P3




MS6H-180CS/CM15B(Z)2-47P5
MS6H-180TL15B(Z)2-47P5




MS6S-100CS/CM30B(Z)2-21P5




MS6H-130CS/CM15B(Z)2-42P3
MS6H-130TL15B(Z)2-42P3



MS6H-130CS/CM20B(Z)2-21P5
MS6H-130TL20B(Z)2-21P5




MS6H-180CS/CM15B(Z)2-43P0
MS6H-180TL15B(Z)2-43P0




MS5 Series T/N Curve


MS5G-130STE-CS/CM05415B/BZ-20P8-S01
MS5G-130STE-TL05415B/BZ-20P8-S01




MS5G-130STE-CS/CM10015B-21P5-S01




MS5G-130STE-CS/CM14615B/BZ-22P3-S01
MS5G-130STE-TL14615B/BZ-22P3-S01




MS5S-110STE-CS/CM03230B/BZ-21P0-S01
MS5S-110STE-TL03230B/BZ-21P0-S01




MS5G-130STE-CS/CM07220B/BZ-41P5-S01
MS5G-130STE-TL07220B/BZ-41P5-S01




MS5G-130STE-CS/CM14615B/BZ-42P3-S01
MS5G-130STE-TL14615B/BZ-42P3-S01




MS5S-110STE-CS/CM04830B/BZ-21P5
MS5S-110STE-TL04830B/BZ-21P5




MS5S-110STE-CS/CM06030B/BZ-21P8
MS5S-110STE-TL06030B/BZ-21P8




MS5G-130STE-CS/CM07730B(Z) -22P4-S01
MS5G-130STE-TL07730B(Z) -22P4-S01




MS5G-130STE-CS/CM07220B/BZ-21P5-S01
MS5G-130STE-TL07220B/BZ-21P5-S01




MS5G-130STE-CS/CM11515B/BZ-21P8-S01
MS5G-130STE-TL11515B/BZ-21P8-S01




MS5G-130STE-CS/CM10025B(Z) -22P6-S01




MS5G-130STE-CS/CM06025B-21P5-S01



MS5G-130STE-CS/CM11515B/BZ-41P8-S01
MS5G-130STE-TL11515B/BZ-41P8-S01




MS-130STE-TL10030B/BZ-43P0




MS Series T/N Curve


MS-220STE-TL70015B/BZ-411P0-XJ



MS-220STE-TL96015B/BZ-415P0-XJ



MS5G-220STE-CS/CM140015B-422P0-S01
MS5G-220STE-TL140015B-422P0-S01




Motor Dimension

(Unit: mm)


MS6 series

40 flange

Motor model	LA±1		Inertia level
	Normal	With brake	
MS6H-40C□30B□1-20P1	91	122.9	High inertia




Motor model	LA±1		Inertia level
	Normal	With brake	
MS6H-40□□30B□3-20P1	79.4	112.9	High inertia




60 flange

Motor model	LA±1		Inertia level
	Normal	With brake	
MS6H-60C□30B□1-20P2	90	121	High inertia
MS6S-60C□30B□□-20P4	107	139	Low inertia
MS6H-60C□30B□□-20P4	119	151	High inertia




Motor model	LA±1		Inertia level
	Normal	With brake	
MS6H-60□□30B□3-20P2	76.4	99.15	High inertia
MS6S-60□□30B□3-20P4	98.4	121.15	Low inertia
MS6H-60□□30B□3-20P4	98.4	121.15	High inertia




100 flange

Motor model	LA±1		Inertia level
	Normal	With brake	
MS6S-100□30B2-21P5	158.5	202.4	Low inertia




80 flange

Motor model	LA±1		Inertia level
	Normal	With brake	
MS6S-80C□30B□□-20P7	117	150	Low inertia
MS6H-80C□30B□□-20P7	124	157	High inertia
MS6S-80C□20B□□-20P7	127	160	Low inertia
MS6H-80C□20B□□-20P7	149	182	High inertia




Motor model	LA±1		Inertia level
	Normal	With brake	
MS6S-80□□30B□3-20P7	107.1	132.1	Low inertia
MS6H-80□□30B□3-20P7	107.1	132.1	High inertia
MS6S-80□□30B□3-21P0	117.6	142.6	Low inertia
MS6H-80□□30B□3-21P0	134	159	High inertia



130 flange

Motor model	LA±1		Inertia level
	Normal	With brake	
MS6H-130C□15B□2-20P8	126	156	High inertia
MS6H-130TL15B□2-20P8	142	172	
MS6H-130C□15B□2-40P8	126	156	
MS6H-130TL15B□2-40P8	142	172	
MS6H-130C□15B□2-41P3	148	178	
MS6H-130TL15B□2-41P3	164	194	
MS6H-130C□20B□2-21P5	148	178	
MS6H-130TL20B□2-21P5	164	194	
MS6H-130C□15B□2-21P8	175	205	
MS6H-130TL15B□2-21P8	191	221	
MS6H-130C□15B□2-41P8	175	205	
MS6H-130TL15B□2-41P8	191	221	
MS6H-130C□15B□2-22P3	195.6	225.6	
MS6H-130TL15B□2-22P3	211.6	241.6	
MS6H-130C□15B□2-42P3	195.6	225.6	
MS6H-130TL15B□2-42P3	211.6	241.6	




Motor Dimension

(Unit: mm)


MS6 series

180 flange


Motor model	LA±1		Inertia level
	Normal	With brake	
MS6H-180C□15B2-43P0	215	255	High inertia
MS6H-180TL15B2-43P0	215	255	
MS6H-180C□15B2-44P4	247	287	
MS6H-180TL15B2-44P4	247	287	



Motor model	LA±1		Inertia level
	Normal	With brake	
MS6H-180C□15B2-45P5	269	309	High inertia
MS6H-180TL15B2-45P5	269	309	
MS6H-180C□15B2-47P5	325	365	
MS6H-180TL15B2-47P5	325	365	




Motor model	LA±1		Inertia level
	Normal	With brake	
MS6H-180C□15E2-45P5	269	309	High inertia
MS6H-180C□15E2-47P5	325	365	



MS5/MS series

110 flange


Motor model	LA±1		Inertia level
	Normal	With brake	
MS5S-110STE-C□03230B□-21P0-S01	157	205	Low inertia
MS5S-110STE-C□04830B□-21P5-S01	166	214	
MS5S-110STE-C□06030B□-21P8-S01	181	229	
MS5S-110STE-TL03230B□-21P0-S01	157	205	
MS5S-110STE-TL04830B□-21P5-S01	166	214	




MS5/MS series

130 flange

Motor model	LA±1		LB	Inertia level
	Normal	With brake		
MS5G-130STE-C□05415B□-20P8-S01	117.5	147	12.5	Medium inertia
MS5G-130STE-C□07220B□-21P5-S01	132.5	162.5		
MS5G-130STE-C□07220B□-41P5-S01	132.5	162.5		
MS5G-130STE-C□11515B□-21P8-S01	159.5	189.5		
MS5G-130STE-C□11515B□-41P8-S01	159.5	189.5		
MS5G-130STE-C□14615B□-22P3-S01	180.5	210.5		
MS5G-130STE-C□14615B□-42P3-S01	180.5	210.5		
MS5G-130STE-C□07730B□-22P4-S01	132.5	162.5		
MS5G-130STE-C□10025B□-22P6-S01	159.5	189.5		
MS5G-130STE-TL05415B□-20P8-S01	134.5	164.5		
MS5G-130STE-TL07220B□-21P5-S01	149.5	179.5		
MS5G-130STE-TL07220B□-41P5-S01	149.5	179.5		
MS5G-130STE-TL11515B□-21P8-S01	176.5	206.5		
MS5G-130STE-TL11515B□-41P8-S01	176.5	206.5		
MS5G-130STE-TL14615B□-22P3-S01	197.5	227.5		
MS5G-130STE-TL14615B□-42P3-S01	197.5	227.5		
MS5G-130STE-TL07730B□-22P4-S01	149.5	179.5		




Motor model	LA±1		Inertia level
	Normal	With brake	
MS5G-130STE-C□06025B-21P5-S01	122	153.5	Medium inertia
MS5G-130STE-C□10015B-21P5-S01	145	176.5	



220 flange

Motor model	LA±1		Inertia level
	Normal	With brake	
MS-220STE-TL70015B□-411P0-XJ	454	549	-
MS-220STE-TL96015B□-415P0-XJ	507	602	
MS5G-220STE-□□140015B-422P0-S01	535	-	Medium inertia



Model Selection List

DS5L1/5C1/5N1/5L/5C/5E/5K/5F match MS6-B3 series motor

80 flange and below motors									
Power (kW)	Inertia level	Motor model	Matched driver	Voltage level	Front outgoing cable		Rear outgoing cable		Transfer cable
					Encoder cable	Power cable	Encoder cable	Power cable	Only support front outgoing cable
0.1	High inertia	MS6H-40CS30B3-20P1	DS5L1/C1/N1-20P1-PTA DS5L/E/C/F/K-20P1-PTA	AC 220V	CP(T)-SE-M-Length	CM(T)-E03A-Length	CP(T)-SF-M-Length	CM(T)-F03A-Length	CPT-PE CMT-PE03 CMBT-PE03
		MS6H-40CM30B3-20P1			CP(T)-SE-BM-Length	CM(T)-E03A-Length	CP(T)-SF-BM-Length	CM(T)-F03A-Length	
		MS6H-40CS30BZ3-20P1			CP(T)-SE-M-Length	CMB(T)-E03A-Length	CP(T)-SF-M-Length	CMB(T)-F03A-Length	
		MS6H-40CM30BZ3-20P1			CP(T)-SE-BM-Length	CMB(T)-E03A-Length	CP(T)-SF-BM-Length	CMB(T)-F03A-Length	
0.2	High inertia	MS6H-60CS30B3-20P2	DS5L1/C1/N1-20P2-PTA DS5L/E/C/F/K-20P2-PTA		CP(T)-SE-M-Length	CM(T)-E05A-Length	CP(T)-SF-M-Length	CM(T)-F05A-Length	CPT-PE CMT-PE05 CMBT-PE05
		MS6H-60CM30B3-20P2			CP(T)-SE-BM-Length	CM(T)-E05A-Length	CP(T)-SF-BM-Length	CM(T)-F05A-Length	
		MS6H-60CS30BZ3-20P2			CP(T)-SE-M-Length	CMB(T)-E05A-Length	CP(T)-SF-M-Length	CMB(T)-F05A-Length	
		MS6H-60CM30BZ3-20P2			CP(T)-SE-BM-Length	CMB(T)-E05A-Length	CP(T)-SF-BM-Length	CMB(T)-F05A-Length	
0.4	Low inertia	MS6S-60CS30B3-20P4	DS5L1/C1/N1-20P4-PTA DS5L/E/C/F/K-20P4-PTA		CP(T)-SE-M-Length	CM(T)-E05A-Length	CP(T)-SF-M-Length	CM(T)-F05A-Length	
		MS6S-60CM30B3-20P4			CP(T)-SE-BM-Length	CM(T)-E05A-Length	CP(T)-SF-BM-Length	CM(T)-F05A-Length	
		MS6S-60CS30BZ3-20P4			CP(T)-SE-M-Length	CMB(T)-E05A-Length	CP(T)-SF-M-Length	CMB(T)-F05A-Length	
		MS6S-60CM30BZ3-20P4			CP(T)-SE-BM-Length	CMB(T)-E05A-Length	CP(T)-SF-BM-Length	CMB(T)-F05A-Length	
	High inertia	MS6H-60CS30B3-20P4			CP(T)-SE-M-Length	CM(T)-E05A-Length	CP(T)-SF-M-Length	CM(T)-F05A-Length	
		MS6H-60CM30B3-20P4			CP(T)-SE-BM-Length	CM(T)-E05A-Length	CP(T)-SF-BM-Length	CM(T)-F05A-Length	
		MS6H-60CS30BZ3-20P4			CP(T)-SE-M-Length	CMB(T)-E05A-Length	CP(T)-SF-M-Length	CMB(T)-F05A-Length	
		MS6H-60CM30BZ3-20P4			CP(T)-SE-BM-Length	CMB(T)-E05A-Length	CP(T)-SF-BM-Length	CMB(T)-F05A-Length	
0.75	Low inertia	MS6S-80CS30B3-20P7	DS5L1/C1/N1-20P7-PTA DS5L/E/C/F/K-20P7-PTA		CP(T)-SE-M-Length	CM(T)-E05A-Length	CP(T)-SF-M-Length	CM(T)-F05A-Length	CPT-PE CMT-PE05 CMBT-PE05
		MS6S-80CM30B3-20P7			CP(T)-SE-BM-Length	CM(T)-E05A-Length	CP(T)-SF-BM-Length	CM(T)-F05A-Length	
		MS6S-80CS30BZ3-20P7			CP(T)-SE-M-Length	CMB(T)-E05A-Length	CP(T)-SF-M-Length	CMB(T)-F05A-Length	
		MS6S-80CM30BZ3-20P7			CP(T)-SE-BM-Length	CMB(T)-E05A-Length	CP(T)-SF-BM-Length	CMB(T)-F05A-Length	
	High inertia	MS6H-80CS30B3-20P7			CP(T)-SE-M-Length	CM(T)-E05A-Length	CP(T)-SF-M-Length	CM(T)-F05A-Length	
		MS6H-80CM30B3-20P7			CP(T)-SE-BM-Length	CM(T)-E05A-Length	CP(T)-SF-BM-Length	CM(T)-F05A-Length	
		MS6H-80CS30BZ3-20P7			CP(T)-SE-M-Length	CMB(T)-E05A-Length	CP(T)-SF-M-Length	CMB(T)-F05A-Length	
		MS6H-80CM30BZ3-20P7			CP(T)-SE-BM-Length	CMB(T)-E05A-Length	CP(T)-SF-BM-Length	CMB(T)-F05A-Length	
1	Low inertia	MS6S-80CS30B3-21P0	DS5L1/C1/N1-20P7-PTA DS5L/E/C/F/K-20P7-PTA		CP(T)-SE-M-Length	CM(T)-E05A-Length	CP(T)-SF-M-Length	CM(T)-F05A-Length	CPT-PE CMT-PE05 CMBT-PE05
		MS6S-80CM30B3-21P0			CP(T)-SE-BM-Length	CM(T)-E05A-Length	CP(T)-SF-BM-Length	CM(T)-F05A-Length	
		MS6S-80CS30BZ3-21P0			CP(T)-SE-M-Length	CMB(T)-E05A-Length	CP(T)-SF-M-Length	CMB(T)-F05A-Length	
		MS6S-80CM30BZ3-21P0			CP(T)-SE-BM-Length	CMB(T)-E05A-Length	CP(T)-SF-BM-Length	CMB(T)-F05A-Length	
	High inertia	MS6H-80CS30B3-21P0			CP(T)-SE-M-Length	CM(T)-E05A-Length	CP(T)-SF-M-Length	CM(T)-F05A-Length	
		MS6H-80CM30B3-21P0			CP(T)-SE-BM-Length	CM(T)-E05A-Length	CP(T)-SF-BM-Length	CM(T)-F05A-Length	
		MS6H-80CS30BZ3-21P0			CP(T)-SE-M-Length	CMB(T)-E05A-Length	CP(T)-SF-M-Length	CMB(T)-F05A-Length	
		MS6H-80CM30BZ3-21P0			CP(T)-SE-BM-Length	CMB(T)-E05A-Length	CP(T)-SF-BM-Length	CMB(T)-F05A-Length	

* Note: 1. Please select one between front outgoing cable and rear outgoing cable.
2. The connection cable please select one between CMT and CMBT, non-brake model please select CMT, brake model please select CMBT.

Model Selection List

MS6 series

DS5L/5C/5E/5K/5F								
Power (kW)	Inertia level	Motor model	Matched driver	Voltage level	Encoder cable	Power cable	Brake cable	Cable accessories package
0.1	High inertia	MS6H-40CS30B1-20P1	DS5L/E/C/F/K-20P1-PTA	AC 220V	CP(T)-SP-M-Length	CM(T)-P07-M-Length	/	JAM-P9-P4
		MS6H-40CM30B1-20P1			CP(T)-SP-BM-Length	CM(T)-P07-M-Length	/	JAM-P9-P4
		MS6H-40CS30BZ1-20P1			CP(T)-SP-M-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6H-40CM30BZ1-20P1			CP(T)-SP-BM-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
0.2	High inertia	MS6H-60CS30B1-20P2	DS5L/E/C/F/K-20P2-PTA		CP(T)-SP-M-Length	CM(T)-P07-M-Length	/	JAM-P9-P4
		MS6H-60CM30B1-20P2			CP(T)-SP-BM-Length	CM(T)-P07-M-Length	/	JAM-P9-P4
		MS6H-60CS30BZ1-20P2			CP(T)-SP-M-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6H-60CM30BZ1-20P2			CP(T)-SP-BM-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
0.4	Low inertia	MS6S-60CS30B1-20P4	DS5L/E/C/F/K-20P4-PTA		CP(T)-SP-M-Length	CM(T)-P07-M-Length	/	JAM-P9-P4
		MS6S-60CM30B1-20P4			CP(T)-SP-BM-Length	CM(T)-P07-M-Length	/	JAM-P9-P4
		MS6S-60CS30BZ1-20P4			CP(T)-SP-M-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6S-60CM30BZ1-20P4			CP(T)-SP-BM-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
	High inertia	MS6H-60CS30B1-20P4			CP(T)-SP-M-Length	CM(T)-P07-M-Length	/	JAM-P9-P4
		MS6H-60CM30B1-20P4			CP(T)-SP-BM-Length	CM(T)-P07-M-Length	/	JAM-P9-P4
		MS6H-60CS30BZ1-20P4			CP(T)-SP-M-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6H-60CM30BZ1-20P4			CP(T)-SP-BM-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
0.75	Low inertia	MS6S-80CS20B1-20P7	DS5L/E/C/F/K-20P7-PTA		CP(T)-SP-M-Length	CM(T)-P07-M-Length	/	JAM-P9-P4
		MS6S-80CM20B1-20P7			CP(T)-SP-BM-Length	CM(T)-P07-M-Length	/	JAM-P9-P4
		MS6S-80CS20BZ1-20P7			CP(T)-SP-M-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6S-80CM20BZ1-20P7			CP(T)-SP-BM-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
	High inertia	MS6H-80CS20B1-20P7			CP(T)-SP-M-Length	CM(T)-P07-M-Length	/	JAM-P9-P4
		MS6H-80CM20B1-20P7			CP(T)-SP-BM-Length	CM(T)-P07-M-Length	/	JAM-P9-P4
		MS6H-80CS20BZ1-20P7			CP(T)-SP-M-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6H-80CM20BZ1-20P7			CP(T)-SP-BM-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
	Low inertia	MS6S-80CS30B1-20P7			CP(T)-SP-M-Length	CM(T)-P07-M-Length	/	JAM-P9-P4
		MS6S-80CM30B1-20P7			CP(T)-SP-BM-Length	CM(T)-P07-M-Length	/	JAM-P9-P4
		MS6S-80CS30BZ1-20P7			CP(T)-SP-M-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6S-80CM30BZ1-20P7			CP(T)-SP-BM-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
	High inertia	MS6H-80CS30B1-20P7			CP(T)-SP-M-Length	CM(T)-P07-M-Length	/	JAM-P9-P4
		MS6H-80CM30B1-20P7			CP(T)-SP-BM-Length	CM(T)-P07-M-Length	/	JAM-P9-P4
		MS6H-80CS30BZ1-20P7			CP(T)-SP-M-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6H-80CM30BZ1-20P7			CP(T)-SP-BM-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
0.85	High inertia	MS6H-80CM30BZ1-20P7	DS5L/E/C/K/F-21P0-PTA		CP(T)-SP-BM-Length	CM(T)-P07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6H-130CS15B2-20P8			CP(T)-SC-M-Length	CM(T)-L15-Length	/	JAM-C10-L4
		MS6H-130CM15B2-20P8			CP(T)-SC-B-Length	CM(T)-L15-Length	/	JAM-C10-L4
		MS6H-130CS15BZ2-20P8			CP(T)-SC-M-Length	CMB(T)-L15-Length	/	JAM-C10-L7
		MS6H-130CM15BZ2-20P8			CP(T)-SC-B-Length	CMB(T)-L15-Length	/	JAM-C10-L7
		MS6H-130TL15B2-20P8			CP(T)-SC-B-Length	CM(T)-L15-Length	/	JAM-C10-L4
		MS6H-130TL15BZ2-20P8			CP(T)-SC-B-Length	CMB(T)-L15-Length	/	JAM-C10-L7
		MS6H-130CS15B2-40P8			CP(T)-SC-M-Length	CM(T)-L15-Length	/	JAM-C10-L4
1.3	High inertia	MS6H-130CS15BZ2-40P8	DS5E/C/F-41P0-PTA		CP(T)-SC-B-Length	CM(T)-L15-Length	/	JAM-C10-L4
		MS6H-130TL15B2-40P8			CP(T)-SC-B-Length	CMB(T)-L15-Length	/	JAM-C10-L7
		MS6H-130CS15B2-41P3			CP(T)-SC-M-Length	CM(T)-L15-Length	/	JAM-C10-L4
		MS6H-130CM15B2-41P3			CP(T)-SC-B-Length	CM(T)-L15-Length	/	JAM-C10-L4
		MS6H-130CS15BZ2-41P3			CP(T)-SC-M-Length	CMB(T)-L15-Length	/	JAM-C10-L7
		MS6H-130CM15BZ2-41P3			CP(T)-SC-B-Length	CMB(T)-L15-Length	/	JAM-C10-L7
		MS6H-130TL15B2-41P3			CP(T)-SC-B-Length	CM(T)-L15-Length	/	JAM-C10-L4
		MS6H-130TL15BZ2-41P3			CP(T)-SC-M-Length	CM(T)-L15-Length	/	JAM-C10-L4
1.5	Low inertia	MS6S-100CS30B2-21P5	DS5E/L/C/F/K-21P5-PTA		CP(T)-SC-M-Length	CM(T)-L15-Length	/	JAM-C10-L4
		MS6S-100CM30B2-21P5			CP(T)-SC-B-Length	CM(T)-L15-Length	/	JAM-C10-L4
		MS6S-100CS30BZ2-21P5			CP(T)-SC-M-Length	CMB(T)-L15-Length	/	JAM-C10-L7
		MS6S-100CM30BZ2-21P5			CP(T)-SC-B-Length	CMB(T)-L15-Length	/	JAM-C10-L7
	High inertia	MS6H-130CS20B2-21P5			CP(T)-SC-M-Length	CM(T)-L15-Length	/	JAM-C10-L4
		MS6H-130CM20B2-21P5			CP(T)-SC-B-Length	CM(T)-L15-Length	/	JAM-C10-L4
		MS6H-130CS20BZ2-21P5			CP(T)-SC-M-Length	CMB(T)-L15-Length	/	JAM-C10-L7
		MS6H-130CM20BZ2-21P5			CP(T)-SC-B-Length	CMB(T)-L15-Length	/	JAM-C10-L7
1.8	High inertia	MS6H-130TL20B2-21P5	DS5E/L/C/F/K-22P6-PTA	CP(T)-SC-B-Length	CM(T)-L15-Length	/	JAM-C10-L4	
		MS6H-130TL20BZ2-21P5		CP(T)-SC-M-Length	CM(T)-L15-Length	/	JAM-C10-L4	
		MS6H-130CS15B2-21P8		CP(T)-SC-M-Length	CM(T)-L15-Length	/	JAM-C10-L4	
		MS6H-130CM15B2-21P8		CP(T)-SC-B-Length	CM(T)-L15-Length	/	JAM-C10-L4	
		MS6H-130CS15BZ2-21P8		CP(T)-SC-M-Length	CMB(T)-L15-Length	/	JAM-C10-L7	
		MS6H-130CM15BZ2-21P8		CP(T)-SC-B-Length	CMB(T)-L15-Length	/	JAM-C10-L7	
		MS6H-130TL15B2-21P8		CP(T)-SC-B-Length	CM(T)-L15-Length	/	JAM-C10-L4	
		MS6H-130TL15BZ2-21P8		CP(T)-SC-M-Length	CM(T)-L15-Length	/	JAM-C10-L4	
1.8	High inertia	MS6H-130CS15B2-41P8	DS5E/C/K/F-41P5-PTA	AC 380V	CP(T)-SC-M-Length	CMB(T)-L15-Length	/	JAM-C10-L7
		MS6H-130CM15B2-41P8			CP(T)-SC-B-Length	CM(T)-L15-Length	/	JAM-C10-L7
		MS6H-130CS15BZ2-41P8			CP(T)-SC-B-Length	CMB(T)-L15-Length	/	JAM-C10-L7
		MS6H-130TL15B2-41P8			CP(T)-SC-B-Length	CMB(T)-L15-Length	/	JAM-C10-L7

DS5L/5C/5E/5K/5F								
Power (kW)	Inertia level	Motor model	Matched driver	Voltage level	Encoder cable	Power cable	Cable accessories package	
2.3	High inertia	MS6H-130CS15B2-22P3	DS5E/L/C/F/K-22P6-PTA	AC 220V	CP(T)-SC-M-Length	CM(T)-L15-Length	JAM-C10-L4	
		MS6H-130CM15B2-22P3			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4	
		MS6H-130CS15BZ2-22P3			CP(T)-SC-M-Length	CMB(T)-L15-Length	JAM-C10-L7	
		MS6H-130CM15BZ2-22P3			CP(T)-SC-B-Length	CMB(T)-L15-Length	JAM-C10-L7	
		MS6H-130TL15B2-22P3			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4	
		MS6H-130TL15BZ2-22P3			CP(T)-SC-B-Length	CMB(T)-L15-Length	JAM-C10-L7	
		MS6H-130CS15B2-42P3			CP(T)-SC-M-Length	CM(T)-L15-Length	JAM-C10-L4	
		MS6H-130CM15B2-42P3			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4	
		MS6H-130CS15BZ2-42P3			CP(T)-SC-M-Length	CMB(T)-L15-Length	JAM-C10-L7	
		MS6H-130CM15BZ2-42P3			CP(T)-SC-B-Length	CMB(T)-L15-Length	JAM-C10-L7	
3.0	High inertia	MS6H-130TL15B2-42P3	DS5E/C/F/K-43P0-PTA	AC 220V	CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4	
		MS6H-180CS15B2-43P0			CP(T)-SL-M-Length	CM(T)-XL25-Length	JAM-L15-XL4	
		MS6H-180CM15B2-43P0			CP(T)-SL-B-Length	CM(T)-XL25-Length	JAM-L15-XL4	
		MS6H-180CS15BZ2-43P0			CP(T)-SL-M-Length	CMB(T)-XL25-Length	JAM-L15-XL6	
		MS6H-180CM15BZ2-43P0			CP(T)-SL-B-Length	CMB(T)-XL25-Length	JAM-L15-XL6	
		MS6H-180TL15B2-43P0			CP(T)-SL-B-Length	CM(T)-XL25-Length	JAM-L15-XL4	
		MS6H-180TL15BZ2-43P0			CP(T)-SL-B-Length	CMB(T)-XL25-Length	JAM-L15-XL6	
		MS6H-180CS15B2-44P4			CP(T)-SL-M-Length	CM(T)-XL60-Length	JAM-L15-XL4	
		MS6H-180CM15B2-44P4			CP(T)-SL-B-Length	CM(T)-XL60-Length	JAM-L15-XL4	
		MS6H-180CS15BZ2-44P4			CP(T)-SL-M-Length	CMB(T)-XL60-Length	JAM-L15-XL6	
4.4	High inertia	MS6H-180CM15BZ2-44P4	DS5E/C-45P5-PTA-H	AC 380V	CP(T)-SL-B-Length	CMB(T)-XL60-Length	JAM-L15-XL6	
		MS6H-180TL15B2-44P4			CP(T)-SL-B-Length	CM(T)-XL60-Length	JAM-L15-XL4	
		MS6H-180CS15B2-45P5			CP(T)-SL-M-Length	CMB(T)-XL60-Length	JAM-L15-XL6	
		MS6H-180CM15B2-45P5			CP(T)-SL-B-Length	CMB(T)-XL60-Length	JAM-L15-XL6	
		MS6H-180TL15B2-45P5			CP(T)-SL-B-Length	CM(T)-XL60-Length	JAM-L15-XL4	
		MS6H-180TL15BZ2-45P5			CP(T)-SL-B-Length	CMB(T)-XL60-Length	JAM-L15-XL6	
		MS6H-180CS15B2-47P5			CP(T)-SL-M-Length	CM(T)-XL60-Length	JAM-L15-XL4	
		MS6H-180CM15B2-47P5			CP(T)-SL-B-Length	CM(T)-XL60-Length	JAM-L15-XL4	
		MS6H-180CS15BZ2-47P5			CP(T)-SL-M-Length	CMB(T)-XL60-Length	JAM-L15-XL6	
		MS6H-180CM15BZ2-47P5			CP(T)-SL-B-Length	CMB(T)-XL60-Length	JAM-L15-XL6	
5.5	High inertia	MS6H-180CS15E2-47P5	DS5E/C-47P5-PTA-H	AC 220V	CP(T)-SL-B-Length	CM(T)-XL60-Length	JAM-L15-XL4	
		MS6H-180TL15B2-47P5			CP(T)-SV-M-Length	CMT-V07-M-Length	JAM-V7-V4	
		MS6H-180TL15BZ2-47P5			CP(T)-SV-BM-Length	CMT-V07-M-Length	JAM-V7-V4	
		MS6H-180CS15E2-47P5			CP(T)-SV-M-Length	CMT-V07-M-Length	JAM-V7-V4	
		MS6H-180CM15E2-47P5			CP(T)-SV-BM-Length	CMT-V07-M-Length	JAM-V7-V4	
		MS6H-180CS15B2-20P4			CP(T)-SV-M-Length	CMT-V07-M-Length	JAM-V7-V4	
		MS6H-180CM15B2-20P4			CP(T)-SV-BM-Length	CMT-V07-M-Length	JAM-V7-V4	
		MS6H-180CS15BZ2-20P4			CP(T)-SV-M-Length	CMT-V07-M-Length	JAM-V7-V4	
		MS6H-180CM15BZ2-20P4			CP(T)-SV-BM-Length	CMT-V07-M-Length	JAM-V7-V4	
		MS6H-180CS15B2-20P4			CP(T)-SV-M-Length	CMT-V07-M-Length	JAM-V7-V4	
7.5	High inertia	MS6H-180CM15B2-47P5	DS5E/C-47P5-PTA-H	AC 220V	CP(T)-SV-BM-Length	CMT-V07-M-Length	JAM-V7-V6	
		MS6H-180TL15B2-47P5			CP(T)-SV-M-Length	CMT-V07-M-Length	JAM-V7-V6	
		MS6H-180TL15BZ2-47P5			CP(T)-SV-BM-Length	CMT-V07-M-Length	JAM-V7-V6	
		MS6H-180CS15B2-47P5			CP(T)-SV-M-Length	CMT-V07-M-Length	JAM-V7-V6	
		MS6H-180CM15B2-47P5			CP(T)-SV-BM-Length	CMT-V07-M-Length	JAM-V7-V6	
		MS6H-180TL15B2-47P5			CP(T)-SV-M-Length	CMT-V07-M-Length	JAM-V7-V6	
		MS6H-180TL15BZ2-47P5			CP(T)-SV-BM-Length	CMT-V07-M-Length	JAM-V7-V6	
		MS6H-180CS15B2-47P5			CP(T)-SV-M-Length	CMT-V07-M-Length	JAM-V7-V6	
		MS6H-180CM15B2-47P5			CP(T)-SV-BM-Length	CMT-V07-M-Length	JAM-V7-V6	
		MS6H-180TL15B2-47P5			CP(T)-SV-M-Length	CMT-V07-M-Length	JAM-V7-V6	
80 flange and below small aviation plug matching list								
0.4	Low inertia	MS6S-60CS30B2-20P4	DS5L/E/C/F/K-20P4-PTA	AC 220V	CP(T)-SV-M-Length	CMT-V07-M-Length	JAM-V7-V4	
		MS6S-60CM30B2-20P4			CP(T)-SV-BM-Length	CMT-V07-M-Length	JAM-V7-V4	
		MS6S-60CS30BZ2-20P4			CP(T)-SV-M-Length	CMBT-V07-M-Length	JAM-V7-V6	
		MS6S-60CM30BZ2-20P4			CP(T)-SV-BM-Length	CMBT-V07-M-Length	JAM-V7-V6	
	High inertia	MS6H-60CS30B2-20P4			CP(T)-SV-M-Length	CMT-V07-M-Length	JAM-V7-V4	
		MS6H-60CM30B2-20P4			CP(T)-SV-BM-Length	CMT-V07-M-Length	JAM-V7-V4	
		MS6H-60CS30BZ2-20P4			CP(T)-SV-M-Length	CMBT-V07-M-Length	JAM-V7-V6	
		MS6H-60CM30BZ2-20P4			CP(T)-SV-BM-Length	CMBT-V07-M-Length	JAM-V7-V6	
0.75	Low inertia	MS6S-80CS20B2-20P7	DS5L/E/C/F/K-20P7-PTA	AC 220V	CP(T)-SV-M-Length	CMT-V07-M-Length	JAM-V7-V4	
		MS6S-80CM20B2-20P7			CP(T)-SV-BM-Length	CMT-V07-M-Length	JAM-V7-V4	
		MS6S-80CS20BZ2-20P7			CP(T)-SV-M-Length	CMBT-V07-M-Length	JAM-V7-V6	
		MS6S-80CM20BZ2-20P7			CP(T)-SV-BM-Length	CMBT-V07-M-Length	JAM-V7-V6	
		MS6H-80CS20B2-20P7			CP(T)-SV-M-Length	CMT-V07-M-Length	JAM-V7-V4	
		MS6H-80CM20B2-20P7			CP(T)-SV-BM-Length	CMT-V07-M-Length	JAM-V7-V4	
		MS6H-80CS20BZ2-20P7			CP(T)-SV-M-Length	CMBT-V07-M-Length	JAM-V7-V6	
		MS6H-80CM20BZ2-20P7			CP(T)-SV-BM-Length	CMBT-V07-M-Length	JAM-V7-V6	
	High inertia	MS6S-80CS30B2-20P7	DS5L/E/C/F/K-20P7-PTA		AC 220V	CP(T)-SV-M-Length	CMT-V07-M-Length	JAM-V7-V4
		MS6S-80CM30B2-20P7				CP(T)-SV-BM-Length	CMT-V07-M-Length	JAM-V7-V4
		MS6S-80CS30BZ2-20P7				CP(T)-SV-M-Length	CMBT-V07-M-Length	JAM-V7-V6
		MS6S-80CM30BZ2-20P7				CP(T)-SV-BM-Length	CMBT-V07-M-Length	JAM-V7-V6
		MS6H-80CS30B2-20P7				CP(T)-SV-M-Length	CMT-V07-M-Length	JAM-V7-V4
		MS6H-80CM30B2-20P7				CP(T)-SV-BM-Length	CMT-V07-M-Length	JAM-V7-V4
		MS6H-80CS30BZ2-20P7				CP(T)-SV-M-Length	CMBT-V07-M-Length	JAM-V7-V6
		MS6H-80CM30BZ2-20P7				CP(T)-SV-BM-Length	CMBT-V07-M-Length	JAM-V7-V6

Model Selection List

DS5L1/5C1/5N1								
Power (kW)	Inertia level	Motor model	Matched driver	Voltage level	Encoder cable	Power cable	Brake cable	Cable accessories package
0.1	High inertia	MS6H-40CS30B1-20P1	DS5L1/C1/N1-20P1-PTA	AC 220V	CP(T)-SP-M -Length	CM(T)-P07A-M-Length	/	JAM-P9-P4
		MS6H-40CM30B1-20P1			CP(T)-SP-BM -Length	CM(T)-P07A-M-Length	/	JAM-P9-P4
		MS6H-40CS30BZ1-20P1			CP(T)-SP-M -Length	CM(T)-P07A-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6H-40CM30BZ1-20P1			CP(T)-SP-BM -Length	CM(T)-P07A-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
0.2	High inertia	MS6H-60CS30B1-20P2	DS5L1/C1/N1-20P2-PTA		CP(T)-SP-M -Length	CM(T)-P07A-M-Length	/	JAM-P9-P4
		MS6H-60CM30B1-20P2			CP(T)-SP-BM -Length	CM(T)-P07A-M-Length	/	JAM-P9-P4
		MS6H-60CS30BZ1-20P2			CP(T)-SP-M -Length	CM(T)-P07A-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6H-60CM30BZ1-20P2			CP(T)-SP-BM -Length	CM(T)-P07A-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
0.4	High inertia	MS6S-60CS30B1-20P4	DS5L1/C1/N1-20P4-PTA		CP(T)-SP-M -Length	CM(T)-P07A-M-Length	/	JAM-P9-P4
		MS6S-60CM30B1-20P4			CP(T)-SP-BM -Length	CM(T)-P07A-M-Length	/	JAM-P9-P4
		MS6S-60CS30BZ1-20P4			CP(T)-SP-M -Length	CM(T)-P07A-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6S-60CM30BZ1-20P4			CP(T)-SP-BM -Length	CM(T)-P07A-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
	High inertia	MS6H-60CS30B1-20P4			CP(T)-SP-M -Length	CM(T)-P07A-M-Length	/	JAM-P9-P4
		MS6H-60CM30B1-20P4			CP(T)-SP-BM -Length	CM(T)-P07A-M-Length	/	JAM-P9-P4
		MS6H-60CS30BZ1-20P4			CP(T)-SP-M -Length	CM(T)-P07A-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6H-60CM30BZ1-20P4			CP(T)-SP-BM -Length	CM(T)-P07A-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
0.75	Low inertia	MS6S-80CS20B1-20P7	DS5L1/C1/N1-20P7-PTA		CP(T)-SP-M -Length	CM(T)-P07A-M-Length	/	JAM-P9-P4
		MS6S-80CM20B1-20P7			CP(T)-SP-BM -Length	CM(T)-P07A-M-Length	/	JAM-P9-P4
		MS6S-80CS20BZ1-20P7			CP(T)-SP-M -Length	CM(T)-P07A-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6S-80CM20BZ1-20P7			CP(T)-SP-BM -Length	CM(T)-P07A-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
	High inertia	MS6H-80CS20B1-20P7			CP(T)-SP-M -Length	CM(T)-P07A-M-Length	/	JAM-P9-P4
		MS6H-80CM20B1-20P7			CP(T)-SP-BM -Length	CM(T)-P07A-M-Length	/	JAM-P9-P4
		MS6H-80CS20BZ1-20P7			CP(T)-SP-M -Length	CM(T)-P07A-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6H-80CM20BZ1-20P7			CP(T)-SP-BM -Length	CM(T)-P07A-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
	Low inertia	MS6S-80CS30B1-20P7			CP(T)-SP-M -Length	CM(T)-P07A-M-Length	/	JAM-P9-P4
		MS6S-80CM30B1-20P7			CP(T)-SP-BM -Length	CM(T)-P07A-M-Length	/	JAM-P9-P4
		MS6S-80CS30BZ1-20P7			CP(T)-SP-M -Length	CM(T)-P07A-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6S-80CM30BZ1-20P7			CP(T)-SP-BM -Length	CM(T)-P07A-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
	High inertia	MS6H-80CS30B1-20P7			CP(T)-SP-M -Length	CM(T)-P07A-M-Length	/	JAM-P9-P4
		MS6H-80CM30B1-20P7			CP(T)-SP-BM -Length	CM(T)-P07A-M-Length	/	JAM-P9-P4
		MS6H-80CS30BZ1-20P7			CP(T)-SP-M -Length	CM(T)-P07A-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
		MS6H-80CM30BZ1-20P7			CP(T)-SP-BM -Length	CM(T)-P07A-M-Length	CB(T)-P03-Length	JAM-P9-P4-P2
80 flange and below small aviation plug matching list								
0.4	Low inertia	MS6S-60CS30B2-20P4	DS5L1/C1/N1-20P4-PTA	AC 220V	CP(T)-SV-M -Length	CMT-V07A-M-Length	/	JAM-V7-V4
		MS6S-60CM30B2-20P4			CP(T)-SV-BM -Length	CMT-V07A-M-Length	/	JAM-V7-V4
		MS6S-60CS30BZ2-20P4			CP(T)-SV-M -Length	CMBT-V07A-M-Length	/	JAM-V7-V6
		MS6S-60CM30BZ2-20P4			CP(T)-SV-BM -Length	CMBT-V07A-M-Length	/	JAM-V7-V6
	High inertia	MS6H-60CS30B2-20P4			CP(T)-SV-M -Length	CMT-V07A-M-Length	/	JAM-V7-V4
		MS6H-60CM30B2-20P4			CP(T)-SV-BM -Length	CMT-V07A-M-Length	/	JAM-V7-V4
		MS6H-60CS30BZ2-20P4			CP(T)-SV-M -Length	CMBT-V07A-M-Length	/	JAM-V7-V6
		MS6H-60CM30BZ2-20P4			CP(T)-SV-BM -Length	CMBT-V07A-M-Length	/	JAM-V7-V6
0.75	Low inertia	MS6S-80CS20B2-20P7	DS5L1/C1/N1-20P7-PTA		CP(T)-SV-M -Length	CMT-V07A-M-Length	/	JAM-V7-V4
		MS6S-80CM20B2-20P7			CP(T)-SV-BM -Length	CMT-V07A-M-Length	/	JAM-V7-V4
		MS6S-80CS20BZ2-20P7			CP(T)-SV-M -Length	CMBT-V07A-M-Length	/	JAM-V7-V6
		MS6S-80CM20BZ2-20P7			CP(T)-SV-BM -Length	CMBT-V07A-M-Length	/	JAM-V7-V6
	High inertia	MS6H-80CM20B2-20P7			CP(T)-SV-M -Length	CMT-V07A-M-Length	/	JAM-V7-V4
		MS6H-80CS20BZ2-20P7			CP(T)-SV-BM -Length	CMT-V07A-M-Length	/	JAM-V7-V6
		MS6H-80CM20BZ2-20P7			CP(T)-SV-M -Length	CMBT-V07A-M-Length	/	JAM-V7-V6
		MS6H-80CM20BZ2-20P7			CP(T)-SV-BM -Length	CMBT-V07A-M-Length	/	JAM-V7-V6
	Low inertia	MS6S-80CS30B2-20P7			CP(T)-SV-M -Length	CMT-V07A-M-Length	/	JAM-V7-V4
		MS6S-80CM30B2-20P7			CP(T)-SV-BM -Length	CMT-V07A-M-Length	/	JAM-V7-V4
		MS6S-80CS30BZ2-20P7			CP(T)-SV-M -Length	CMBT-V07A-M-Length	/	JAM-V7-V6
		MS6S-80CM30BZ2-20P7			CP(T)-SV-BM -Length	CMBT-V07A-M-Length	/	JAM-V7-V6
	High inertia	MS6H-80CS30B2-20P7			CP(T)-SV-M -Length	CMT-V07A-M-Length	/	JAM-V7-V4
		MS6H-80CM30B2-20P7			CP(T)-SV-BM -Length	CMT-V07A-M-Length	/	JAM-V7-V4
		MS6H-80CS30BZ2-20P7			CP(T)-SV-M -Length	CMBT-V07A-M-Length	/	JAM-V7-V6
		MS6H-80CM30BZ2-20P7			CP(T)-SV-BM -Length	CMBT-V07A-M-Length	/	JAM-V7-V6

MS5/MS Series

DS5L/5C/5E/5K/5F							
Power (kW)	Inertia level	Motor model	Matched driver	Voltage level	Encoder cable	Power cable	Cable accessories package
0.85	Medium inertia	MS5G-130STE-CS05415B-20P8-S01	DS5E/L/C/F/K-20P7-PTA	AC 220V	CP(T)-SC-M-Length	CM(T)-L15A-Length	JAM-C10-L4
		MS5G-130STE-CM05415B-20P8-S01			CP(T)-SC-B-Length	CM(T)-L15A-Length	JAM-C10-L4
		MS5G-130STE-CS05415BZ-20P8-S01			CP(T)-SC-M-Length	CMB(T)-L15A-Length	JAM-C10-L7
		MS5G-130STE-CM05415BZ-20P8-S01			CP(T)-SC-B-Length	CMB(T)-L15A-Length	JAM-C10-L7
		MS5G-130STE-TL05415B-20P8-S01			CP(T)-SC-B-Length	CM(T)-L15A-Length	JAM-C10-L4
1.0	Low inertia	MS5G-130STE-TL05415BZ-20P8-S01			CP(T)-SC-B-Length	CMB(T)-L15A-Length	JAM-C10-L7
		MS5S-110STE-CS03230B□-21P0-S01			CP(T)-SL-M-Length	CM(T)-L15-Length	JAM-L15-L4
1.5	Low inertia	MS5S-110STE-TL03230B□-21P0	DS5E/L/C/F/K-21P5-PTA	AC 220V	CP(T)-SL-B-Length	CM(T)-L15-Length	JAM-L15-L4
		MS5S-110STE-CS04830B□-21P5			CP(T)-SL-B-Length	CM(T)-L15-Length	JAM-L15-L4
		MS5S-110STE-CM04830B□-21P5			CP(T)-SL-M-Length	CM(T)-L15-Length	JAM-L15-L4
		MS5S-110STE-TL04830B□-21P5			CP(T)-SL-B-Length	CM(T)-L15-Length	JAM-L15-L4
		MS5G-130STE-CS06025B-21P5-S01			CP(T)-SC-M-Length	CMB(T)-L15-Length	JAM-C10-L7
	Medium inertia	MS5G-130STE-CM06025B-21P5-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CS06025BZ-21P5-S01			CP(T)-SC-M-Length	CMB(T)-L15-Length	JAM-C10-L7
		MS5G-130STE-CM06025BZ-21P5-S01			CP(T)-SC-B-Length	CMB(T)-L15-Length	JAM-C10-L7
		MS5G-130STE-CS10015B-21P5-S01			CP(T)-SC-M-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CM10015B-21P5-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CS10015BZ-21P5-S01			CP(T)-SC-M-Length	CMB(T)-L15-Length	JAM-C10-L7
		MS5G-130STE-CM10015BZ-21P5-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CS07220B-21P5-S01			CP(T)-SC-M-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CM07220B-21P5-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-TL07220B-21P5-S01			CP(T)-SC-M-Length	CMB(T)-L15-Length	JAM-C10-L7
		MS5G-130STE-TL07220BZ-21P5-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
1.8	Medium inertia	MS5G-130STE-CS11515B-21P8-S01			CP(T)-SC-M-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CM11515B-21P8-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CS11515BZ-21P8-S01			CP(T)-SC-M-Length	CMB(T)-L15-Length	JAM-C10-L7
		MS5G-130STE-CM11515BZ-21P8-S01			CP(T)-SC-B-Length	CMB(T)-L15-Length	JAM-C10-L7
		MS5G-130STE-TL11515B-21P8-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
	Low inertia	MS5G-130STE-TL11515BZ-21P8-S01			CP(T)-SC-B-Length	CMB(T)-L15-Length	JAM-C10-L7
		MS5S-110STE-TL06030B□-21P8			CP(T)-SL-B-Length	CM(T)-L15-Length	JAM-L15-L4
		MS5S-110STE-CS06030B□-21P8			CP(T)-SL-M-Length	CM(T)-L15-Length	JAM-L15-L4
		MS5S-110STE-CM06030B□-21P8			CP(T)-SL-B-Length	CM(T)-L15-Length	JAM-L15-L4
		MS5G-130STE-CS14615B-22P3-S01			CP(T)-SC-M-Length	CM(T)-L15-Length	JAM-C10-L4
2.3	Medium inertia	MS5G-130STE-CM14615B-22P3-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CS14615BZ-22P3-S01			CP(T)-SC-M-Length	CMB(T)-L15-Length	JAM-C10-L7
		MS5G-130STE-CM14615BZ-22P3-S01			CP(T)-SC-B-Length	CMB(T)-L15-Length	JAM-C10-L7
		MS5G-130STE-TL14615B-22P3-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-TL14615BZ-22P3-S01			CP(T)-SC-B-Length	CMB(T)-L15-Length	JAM-C10-L7
2.4	Medium inertia	MS5G-130STE-CS07730B-22P4-S01	DS5E/L/C/F/K-22P3-PTA		CP(T)-SC-M-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CM07730B-22P4-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CS07730BZ-22P4-S01			CP(T)-SC-M-Length	CMB(T)-L15-Length	JAM-C10-L7
		MS5G-130STE-CM07730BZ-22P4-S01			CP(T)-SC-B-Length	CMB(T)-L15-Length	JAM-C10-L7
		MS5G-130STE-TL07730B-22P4-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
2.6	Medium inertia	MS5G-130STE-TL07730BZ-22P4-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CS10025B-22P6-S01			CP(T)-SC-M-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CM10025B-22P6-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CS10025BZ-22P6-S01			CP(T)-SC-M-Length	CMB(T)-L15-Length	JAM-C10-L7
		MS5G-130STE-CM10025BZ-22P6-S01			CP(T)-SC-B-Length	CMB(T)-L15-Length	JAM-C10-L7
1.5	Medium inertia	MS5G-130STE-TL10025-22P6-S01	DS5E/C/K-41P5-PTA	AC 380V	CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CS07220B-41P5-S01			CP(T)-SC-M-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CM07220B-41P5-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CS07220BZ-41P5-S01			CP(T)-SC-M-Length	CMB(T)-L15-Length	JAM-C10-L7
		MS5G-130STE-CM07220BZ-41P5-S01			CP(T)-SC-B-Length	CMB(T)-L15-Length	JAM-C10-L7
	Medium inertia	MS5G-130STE-TL07220B-41P5-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-TL07220BZ-41P5-S01			CP(T)-SC-M-Length	CMB(T)-L15-Length	JAM-C10-L7
		MS5G-130STE-CS11515B-41P8-S01			CP(T)-SC-M-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CM11515B-41P8-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-CS11515BZ-41P8-S01			CP(T)-SC-M-Length	CMB(T)-L15-Length	JAM-C10-L7
1.8	Medium inertia	MS5G-130STE-CM11515BZ-41P8-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4
		MS5G-130STE-TL11515B-41P8-S01			CP(T)-SC-M-Length	CMB(T)-L15-Length	JAM-C10-L7
		MS5G-130STE-TL11515BZ-41P8-S01			CP(T)-SC-B-Length	CMB(T)-L15-Length	JAM-C10-L7

Model Selection List

Power (kW)	Inertia level	Motor model	Matched driver	Voltage level	Encoder cable	Power cable	Cable accessories package	
2.3	Medium inertia	MS5G-130ST-CS14615B-42P3-S01	DS5E/C/F/K-43P0-PTA	AC 380V	CP(T)-SC-M-Length	CM(T)-L15-Length	JAM-C10-L4	
		MS5G-130ST-CM14615B-42P3-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4	
		MS5G-130ST-CS14615BZ-42P3-S01			CP(T)-SC-M-Length	CMB(T)-L15-Length	JAM-C10-L7	
		MS5G-130ST-CM14615BZ-42P3-S01			CP(T)-SC-B-Length	CMB(T)-L15-Length	JAM-C10-L7	
		MS5G-130ST-TL14615B-42P3-S01			CP(T)-SC-B-Length	CM(T)-L15-Length	JAM-C10-L4	
		MS5G-130ST-TL14615BZ-42P3-S01			CP(T)-SC-B-Length	CMB(T)-L15-Length	JAM-C10-L7	
3	/	MS-130ST-TL10030B(Z)-43P0			CP(T)-SL-B-Length	CM(T)-L15-Length	JAM-L15-L4	
11	/	MS-220STE-TL70015B□-411P0-XJ	DS5E/C/C1/K1-411P0-PTA			CPT-ZDL-B-Length	CM(T)-D60-Length	/
15	/	MS-220STE-TL96015B□-415P0-XJ	DS5E/C/C1/K1-415P0-PTA			CPT-ZDL-B-Length	CM(T)-D60-Length	
22	Medium inertia	MS5G-220STE-CS/CM140015B-422P0-S01	DS5E-422P0-PTA			CPT-ZDL-B-Length	CM-D100-Length	
		MS5G-220STE-TL140015B-422P0-S01				CPT-ZDL-B-Length	CM-D100-Length	

DS5L1/5C1/5N1						
Power (kW)	Inertia level	Motor model	Matched driver	Voltage level	Encoder cable	Power cable
0.85	High inertia	MS5G-130STE-CS05415B-20P8-S01	DS5L1/C1/N1-20P7-PTA	AC 220V	CP(T)-SC-M-Length	CM(T)-L15B-Length
		MS5G-130STE-CM05415B-20P8-S01			CP(T)-SC-B-Length	CM(T)-L15B-Length
		MS5G-130STE-CS05415BZ-20P8-S01			CP(T)-SC-M-Length	CMB(T)-L15B-Length
		MS5G-130STE-CM05415BZ-20P8-S01			CP(T)-SC-B-Length	CMB(T)-L15B-Length
		MS5G-130STE-TL05415B-20P8-S01			CP(T)-SC-B-Length	CM(T)-L15B-Length
		MS5G-130STE-TL05415BZ-20P8-S01			CP(T)-SC-B-Length	CMB(T)-L15B-Length

Product Accessories

Quick connector

- Provide convenient wiring terminals
- Used by 100W ~ 15kW drivers
- Suitable for DS5F, DS5K series 44 bits terminal: DTHDB44M-BK10



X-NET module

- Bus module: JA-NE-L
- Twisted pair shielded cable for bus module: JC-EA-Length



Battery box

- Battery box model: CP-B-BATT
- The battery cannot be charged



JC-CB bus wiring cable

- Special communication cable for EtherCAT motion bus
- Special communication cable for EtherCAT motion bus



B3 AMP conversion cable

- Power cable
- Encoder cable



Power cable

Encoder cable

DB9 side cable

- Cable specification is 1.5m
- Connect to the PC to control the servo



Power cable

- Cable specification: 2/3/5/8/10/12/16/20/25/30m
- The length can be customized
- Cable connectors can be purchased optionally (excluding cables)




Encoder cable

- Cable specification: 2/3/5/8/10/12/16/20/25/30m
- The length can be customized
- Cable connectors can be purchased optionally (excluding cables)




Regenerative resistor

- Release bus capacitor regeneration voltage
- Refer to the selection table of regenerative resistance in the user manual for specific selection



Differential module

- Realize the conversion of collector signal and differential signal
- Differential to differential isolation circuit board: JS-ID-AB
- Differential to collector circuit board: JS-IDC-AB(AB phase), JS-IDC-ABZ(ABZ phase)



Two in one servo system

More accurate positioning / Faster response
Support gantry synchronization

DM5F series

- Flat appearance structure design, convenient wiring and saving installation space
- Support gantry synchronization and realize double-axis accurate synchronization
- Support Modbus RTU, EtherCAT and CANopen communication protocols
- More accurate positioning and faster response
- Support position, speed, torque mode, multi-mode seamless switching

Power: 0.1kW~1.0kW
Interface: pulse, RS232, RS485
Control mode: position control, speed control, torque control



*Note: Refer to the subsequent list for the models that have been put into operation. Some models have not been put into operation. Please look forward to it.

Naming Rule

DM 5□ - 2□P□ - □ A

①	②	③	④	⑤	⑥
Display	Product name	Display	Product series	Display	Rated input voltage
DM	Multi-axis servo driver	5F	Full function type	1	DC24V~80V
		5C	EtherCAT type	2	AC220V
				3	AC380V
⑤	⑥	Display	Axis quantity	Display	Power
2		A	2 axes	0P4	400W
3			3 axes	0P7	750W
③	④	Display	Design number	Display	Power
		A	Design no. A		

*Note: 750W driver can match the motor of 400W and 750W.


Driver Model List

Series	Driver name	Rated power (W)	DI quantity	DO quantity
DM5 series AC220V	DM5F-20P4-2A	400	6	6
	DM5F-20P7-2A	750	6	6

Driver Specification

Item		DM5F series general model	
Basic specification	Power range	0.1kW~1kW	
	Input power supply	Single phase/three-phase 200~240V, 50~60Hz	
	Encoder feedback	17-bit/23-bit communication encoder	
	Control mode	Three-phase full wave rectifier IPM, PWM control, sine wave current drive mode	
	Ambient temperature	Operation: -10°C~40°C (no condensation)/storage: -20°C~60°C (no condensation)	
	Ambient humidity	Operation/storage: below 90% (no condensation)	
	Vibration and impact resistance	4.9m/s ² / 19.6m/s ²	
	Installation place	Places without dust, dry, vibration and corrosive substances	
	Installation mode	Vertical or horizontal installation	
	Protection function	Overvoltage, undervoltage, overheating, overcurrent, overload, overspeed, analog input abnormality, excessive position deviation, output short circuit, encoder abnormality, regeneration abnormality protection, overtravel protection, oscillation protection, phase loss protection, etc	
	Dynamic brake	No	
	Communication	RS232: standard ModbusRTU protocol RS485: standard ModbusRTU protocol	
	Brake resistor	Built-in brake resistor, can connect external brake resistor	
	Display and operate	5 digits LED indicator light, power indicator, 2 operation indicators and 5 keys	
IO signal	Output state	ABZ differential feedback output	
	Frequency division function	Yes	
	Collector Z phase output	Yes	
	Digital input	6 channels digital input Servo enable, alarm clear, no forward rotation, no reverse rotation, torque limit selection, internal speed selection, gear ratio switching, mode switching, pulse input prohibition, position deviation clear, internal position step change signal	
Position control mode	Digital output	6 channels digital output Positioning completed, servo ready, alarm output, speed arrival, rotation detection, torque limit output, same speed detection, brake release output and frequency division output	
	Pulse direction control	Support P+D, AB phase, CW/CCW	
	Max pulse frequency	Collector open: 200kpps, differential input 500kpps	
	Pulse command mode	3.3~5V/18~24V pulse+direction, AB phase pulse, CW/CCW signal	
Speed control mode	Control mode	External pulse, internal position	
	Feedforward compensation	0~100% (set the resolution to 1%)	
	Positioning completion width	0~65535 command unit (set the resolution to 1 command unit)	
	Electronic gear ratio	1/10000≤B/A≤10000	
Torque control mode	Control mode	Internal 3-segment speed, external speed mode	
	Command smooth mode	Low pass filter, smoothing filter	
	Analog input	No	
	Torque limit	Internal parameter	
Torque control mode	Speed change rate	When the external load rated change is 0~100% of load: below ±0.01% (at rated speed) Rated voltage ±10%: ±0.01% (at rated speed) Ambient temperature 20±25°C: below ±0.01% (at rated speed)	
	Control mode	Internal torque	
	Analog input	No	
Torque control mode	Speed limit	Internal parameter	

Peripheral Wiring Diagram



Terminal definition

① CN3 port (RS232)

Pin	Name	Explanation
1	TXD	RS232 send
2	RXD	RS232 receive
3	GND	RS232 signal ground

② Main circuit terminals

Terminal	Function	Explanation
L1/L2/L3	Main circuit power supply input terminal	Single/three phase AC 200~240V, 50/60Hz
P+/D/C	Use built-in regenerative resistor	Short circuit P+ and D, disconnect P+ and C
	Use external regenerative resistor	Connect the regeneration resistance to P+ and C, remove the short connectors of P+ and D, and set P0-25=power value, P0-26=resistor value
P+/P-	Bus terminal	The real-time voltage of the bus can be measured, please pay attention

③ CN0 port

Pin	Name	Explanation	Pin	Name	Explanation
1	P1-	Axis 1 pulse -	23	SI5	Input terminal
2	P1+5	Axis 1 pulse +5V	24	SI6	High speed input terminal
3	P1+24	Axis 1 pulse +24V	25	+24V	Common terminal of input
4	D1-	Axis 1 direction -	26	SO1-2	Axis 2 output terminal (500mA)
5	D1+5	Axis 1 direction +5V	27	SO2-2	Axis 2 output terminal (50mA)
6	D1+24	Axis 1 direction +24V	28	SO3-2	Axis 2 output terminal (50mA)
7	SI1	Input terminal	29	COM	Common terminal of output
8	SI2	Input terminal	30	NC	Vacant terminal
9	SI3	High speed input terminal	31	OA1+	Axis 1 encoder frequency division output OA+
10	+24V	Common terminal of input	32	OA1-	Axis 1 encoder frequency division output OA-
11	SO1-1	Axis 1 output terminal (500mA)	33	OB1+	Axis 1 encoder frequency division output OB+
12	SO2-1	Axis 1 output terminal (50mA)	34	OB1-	Axis 1 encoder frequency division output OB-
13	SO3-1	Axis 1 output terminal (50mA)	35	OZ1+	Axis 1 encoder frequency division output OZ1+
14	COM	Common terminal of output	36	OZ1-	Axis 1 encoder frequency division output OZ1-
15	NC	Vacant terminal	37	GND	Frequency division output ground
16	P2-	Axis 2 pulse -	38	OA2+	Axis 2 encoder frequency division output OA+
17	P2+5	Axis 2 pulse +5V	39	OA2-	Axis 2 encoder frequency division output OA-
18	P2+24	Axis 2 pulse +24V	40	OB2+	Axis 2 encoder frequency division output OB+
19	D2-	Axis 2 direction -	41	OB2-	Axis 2 encoder frequency division output OB-
20	D2+5	Axis 2 direction +5V	42	OZ2+	Axis 2 encoder frequency division output OZ+
21	D2+24	Axis 2 direction +24V	43	OZ2-	Axis 2 encoder frequency division output OZ-
22	SI4	Input terminal	44	GND	Frequency division output ground

④ CN2 port


Pin	Name
1	5V
2	GND
3	/
4	/
5	485-A
6	485-B

⑤ CN1 port (from down to up)

Pin	Name	Pin	Name
1	/	7	/
2	/	8	/
3	/		
4	485-A		
5	485-B		
6	485-GND		

⑥ Motor power terminals

Pin	Name
1	V
2	U
3	W
4	PE



Driver Motor Matching List


DM5F matched MS6 motor

Power (kW)	Inertia level	Motor model	Matched driver	Voltage level	Encoder cable	Power cable	Brake cable	Cable accessories package
0.2	High inertia	MS6H-60CS30B1-20P2	DM5F-20P4-2A	AC 220V	CP(T)-SP-M-Length	CM(T)-PP07-M-Length	/	JAM-P9-P4-P4
		MS6H-60CM30B1-20P2			CP(T)-SP-BM-Length	CM(T)-PP07-M-Length	/	JAM-P9-P4-P4
		MS6H-60CS30BZ1-20P2			CP(T)-SP-M-Length	CM(T)-PP07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P4-P2
		MS6H-60CM30BZ1-20P2			CP(T)-SP-BM-Length	CM(T)-PP07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P4-P2
0.4	Low inertia	MS6S-60CS30B1-20P4	DM5F-20P4/20P7-2A		CP(T)-SP-M-Length	CM(T)-PP07-M-Length	/	JAM-P9-P4-P4
		MS6S-60CM30B1-20P4			CP(T)-SP-BM-Length	CM(T)-PP07-M-Length	/	JAM-P9-P4-P4
		MS6S-60CS30BZ1-20P4			CP(T)-SP-M-Length	CM(T)-PP07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P4-P2
		MS6S-60CM30BZ1-20P4			CP(T)-SP-BM-Length	CM(T)-PP07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P4-P2
	High inertia	MS6H-60CS30B1-20P4			CP(T)-SP-M-Length	CM(T)-PP07-M-Length	/	JAM-P9-P4-P4
		MS6H-60CM30B1-20P4			CP(T)-SP-BM-Length	CM(T)-PP07-M-Length	/	JAM-P9-P4-P4
		MS6H-60CS30BZ1-20P4			CP(T)-SP-M-Length	CM(T)-PP07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P4-P2
		MS6H-60CM30BZ1-20P4			CP(T)-SP-BM-Length	CM(T)-PP07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P4-P2
0.75	Low inertia	MS6S-80CS20B1-20P7	DM5F-20P7-2A		CP(T)-SP-M-Length	CM(T)-PP07-M-Length	/	JAM-P9-P4-P4
		MS6S-80CM20B1-20P7			CP(T)-SP-BM-Length	CM(T)-PP07-M-Length	/	JAM-P9-P4-P4
		MS6S-80CS20BZ1-20P7			CP(T)-SP-M-Length	CM(T)-PP07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P4-P2
		MS6S-80CM20BZ1-20P7			CP(T)-SP-BM-Length	CM(T)-PP07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P4-P2
		MS6H-80CS20B1-20P7			CP(T)-SP-M-Length	CM(T)-PP07-M-Length	/	JAM-P9-P4-P4
		MS6H-80CM20B1-20P7			CP(T)-SP-BM-Length	CM(T)-PP07-M-Length	/	JAM-P9-P4-P4
		MS6H-80CS20BZ1-20P7			CP(T)-SP-M-Length	CM(T)-PP07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P4-P2
		MS6H-80CM20BZ1-20P7			CP(T)-SP-BM-Length	CM(T)-PP07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P4-P2
	High inertia	MS6S-80CS30B1-20P7			CP(T)-SP-M-Length	CM(T)-PP07-M-Length	/	JAM-P9-P4-P4
		MS6S-80CM30B1-20P7			CP(T)-SP-BM-Length	CM(T)-PP07-M-Length	/	JAM-P9-P4-P4
		MS6S-80CS30BZ1-20P7			CP(T)-SP-M-Length	CM(T)-PP07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P4-P2
		MS6S-80CM30BZ1-20P7			CP(T)-SP-BM-Length	CM(T)-PP07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P4-P2
		MS6H-80CS30B1-20P7			CP(T)-SP-M-Length	CM(T)-PP07-M-Length	/	JAM-P9-P4-P4
		MS6H-80CM30B1-20P7			CP(T)-SP-BM-Length	CM(T)-PP07-M-Length	/	JAM-P9-P4-P4
		MS6H-80CS30BZ1-20P7			CP(T)-SP-M-Length	CM(T)-PP07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P4-P2
		MS6H-80CM30BZ1-20P7			CP(T)-SP-BM-Length	CM(T)-PP07-M-Length	CB(T)-P03-Length	JAM-P9-P4-P4-P2
80 flange and below small aviation plug model matching list								
0.2	High inertia	MS6H-60CS30B1-20P2	DM5F-20P4-2A	AC 220V	CP(T)-SV-M-Length	CMT-PV07-M-Length	/	JAM-V7-V4-P4
		MS6H-60CM30B1-20P2			CP(T)-SV-BM-Length	CMT-PV07-M-Length	/	JAM-V7-V4-P4
		MS6H-60CS30BZ1-20P2			/	/	/	JAM-V7-V6-P4
		MS6H-60CM30BZ1-20P2			/	/	/	JAM-V7-V6-P4
0.4	Low inertia	MS6S-60CS30B2-20P4	CP(T)-SV-M-Length		CMT-PV07-M-Length	/	JAM-V7-V4-P4	
		MS6S-60CM30B2-20P4	CP(T)-SV-BM-Length		CMT-PV07-M-Length	/	JAM-V7-V4-P4	
		MS6S-60CS30BZ2-20P4	/		/	/	JAM-V7-V6-P4	
		MS6S-60CM30BZ2-20P4	/		/	/	JAM-V7-V6-P4	
	High inertia	MS6H-60CS30B2-20P4	CP(T)-SV-M-Length		CMT-PV07-M-Length	/	JAM-V7-V4-P4	
		MS6H-60CM30B2-20P4	CP(T)-SV-BM-Length		CMT-PV07-M-Length	/	JAM-V7-V4-P4	
		MS6H-60CS30BZ2-20P4	/		/	/	JAM-V7-V6-P4	
		MS6H-60CM30BZ2-20P4	/		/	/	JAM-V7-V6-P4	
0.75	Low inertia	MS6S-80CS20B2-20P7	DM5F-20P7-2A		CP(T)-SV-M-Length	CMT-PV07-M-Length	/	JAM-V7-V4-P4
		MS6S-80CM20B2-20P7			CP(T)-SV-BM-Length	CMT-PV07-M-Length	/	JAM-V7-V4-P4
		MS6S-80CS20BZ2-20P7			/	/	/	JAM-V7-V6-P4
		MS6S-80CM20BZ2-20P7			/	/	/	JAM-V7-V6-P4
		MS6H-80CS20B2-20P7			CP(T)-SV-M-Length	CMT-PV07-M-Length	/	JAM-V7-V4-P4
		MS6H-80CM20B2-20P7			CP(T)-SV-BM-Length	CMT-PV07-M-Length	/	JAM-V7-V4-P4
		MS6H-80CS20BZ2-20P7			/	/	/	JAM-V7-V6-P4
		MS6H-80CM20BZ2-20P7			/	/	/	JAM-V7-V6-P4
	High inertia	MS6S-80CS30B2-20P7			CP(T)-SV-M-Length	CMT-PV07-M-Length	/	JAM-V7-V4-P4
		MS6S-80CM30B2-20P7			CP(T)-SV-BM-Length	CMT-PV07-M-Length	/	JAM-V7-V4-P4
		MS6S-80CS30BZ2-20P7			/	/	/	JAM-V7-V6-P4
		MS6S-80CM30BZ2-20P7			/	/	/	JAM-V7-V6-P4
		MS6H-80CS30B2-20P7			CP(T)-SV-M-Length	CMT-PV07-M-Length	/	JAM-V7-V4-P4
		MS6H-80CM30B2-20P7			CP(T)-SV-BM-Length	CMT-PV07-M-Length	/	JAM-V7-V4-P4
		MS6H-80CS30BZ2-20P7			/	/	/	JAM-V7-V6-P4
		MS6H-80CM30BZ2-20P7			/	/	/	JAM-V7-V6-P4

Installation Dimension

(Unit: mm)

DM5F-20P4-2A, DM5F-20P7-2A



Low voltage servo system

Light and compact / Easy to install and debug

Xinje's low-voltage servo system, which can be used for AGV/RGV trolley, adopts low-voltage servo motor for its motion axis, which can provide different motor power options of 0.1kW~1.5kW according to the load size, so as to realize rapid response, high stability and high-precision control in the whole motion control process. Through the cooperative movement between motors, it can realize accurate walking and reversing, and provide a solid and reliable solution for the realization of intelligent logistics.



*Note: Refer to the model list for the models that have been put into operation. Some models have not been put into operation. Please look forward to it.

DF3E Driver

Interface: pulse, RS232, RJ45
Input output: 4 inputs 3 outputs (non-brake model), 3 inputs 3 outputs (brake model)
Control mode: position control, speed control, torque control, bus control



- 1 Appearance innovation**
The new appearance design, rich interfaces, small volume and light body meet the equipment installation requirements of AGV industry
- 2 Powerful function**
Support a variety of control modes, with 24V brake output, alarm synchronous braking and other functions to meet customer requirements
- 3 Diverse communication**
Support EtherCAT, CANopen, MODBUS and other communication protocols to meet different communication function requirements of users
- 4 Convenient debugging**
The gain adjustment only needs three steps, which greatly reduces the equipment debugging time and greatly improves the on-site debugging efficiency

MF3S Low Inertia Motor

Power: 0.4~0.75kW
Using occasion: light load high speed positioning



- 1 Overload capacity**
The whole series is equipped with 3 times overload as standard, and the start and stop in heavy load situations are faster and more stable
- 2 Accuracy assurance**
The motor is equipped with self-developed 17-bit magnetic encoder, and the positioning accuracy is greatly improved
- 3 Excellent performance**
The insulation level reaches the highest level F in the industry, which fully ensures the stability of field application
- 4 Protective ability**
The protection grade reaches IP66, which can easily deal with the occasions with harsh environment such as oil, water vapor and dust, so as to ensure the reliability of the motor

Naming Rule

Low voltage servo driver

DF 3 E - 04 10 Z

① ② ③ ④ ⑤ ⑥

① Name

Display	Product name
DF	Low voltage servo driver

② Series no.

Display	Specification
3	Series no.

③ Control function

Display	Function
E	Pulse, RS485, CANopen
C	EtherCAT type

④ Driver power

Display	Rated output power
01	100W
02	200W
04	400W
07	750W
15	1.5kW

⑤ Rated current

Display	Rated output current
03	3A
05	5A
10	10A
20	20A
40	40A

⑥ Driver function

Display	Driver function
Z	Servo can drive the brake directly
Vacant	Cannot drive the brake directly

Low voltage servo motor

MF3S - 60 C S 30 B Z □ - 5 04

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

① Type		② Base no.		③ Encoder type		④ Encoder precision		⑤ Rated speed	
Display	Inertia	Display	Base no.	Display	Type	Display	Specification	Display	Rated speed
MF3S	Low inertia	40	40 flange	C	Magnetic encoder	S	Single turn 17-bit	15	1500rpm
MF3G	Medium inertia	60	60 flange	T	Photoelectric encoder	M	Multi-turn 17-bit	20	2000rpm
MF3H	High inertia	80	80 flange			L	Multi-turn 23-bit	30	3000rpm
		130	130 flange						

⑥ Motor shaft specification		⑦ Power loss brake		⑧ Motor connector type		⑨ Voltage level		⑩ Rated power	
Display	Shaft key, oil seal	Display	Specification	Display	Plug type	Display	Plug type	Display	Power
A	With key, no oil seal	Z	With brake	1	AMP plug	2	24V	01	100W
B	With key, with oil seal	Vacant	Without brake	2	Aviation plug	5	48V	02	200W
C	No key, no oil seal					6	60V	04	400W
D	No key, with oil seal							07	750W
								15	1.5kW

Low voltage servo cable

CP - SP - M - Length

① ② ③ ④

① Cable type		② Plug type		③ Battery box type		④ Cable length	
Symbol	Cable specification	Symbol	Plug specification	Symbol	Battery box type	Symbol	Length (m)
CP	Normal encoder cable	SP	9-core AMP plug	M	Without battery box	02	2
CPT	High flexibility encoder cable	SV	7-core waterproof small aviation plug	BM	With battery box	03	3
		SC	10-core small aviation plug			05	5

Naming Rule

Low voltage servo cable

CM - P 15 - Length

① ② ③ ④

① Cable type		② Plug type		③ Cable diameter type		④ Cable length	
Symbol	Cable specification	Symbol	Plug specification	Symbol	Cable diameter (mm ²)	Symbol	Length (m)
CM	Normal power cable	P	4-core AMP plug	07	0.75	02	2
CMT	High flexibility power cable	V	4-core waterproof small aviation plug	15	1.5	03	3
CMB	Normal brake power cable			20	2	05	5
CMBT	High flexibility brake power cable	XL	6-core aviation plug	60	6		

Model List

Low voltage servo driver

Series	Driver name	Power (W)	Max continuous output current (A)	Peak current (A)	Control mode
DF3 series DC24~70V	DF3E-0103	100	3	10	RS485, pulse, CANopen
	DF3E-0205	200	5	15	RS485, pulse, CANopen
	DF3E-0410	400	10	30	RS485, pulse, CANopen
	DF3E-0720	750	20	60	RS485, pulse, CANopen
	DF3E-1540	1500	40	120	RS485, pulse, CANopen

Low voltage servo motor


Series	Power supply voltage (V)	Model	Power (W)	Rated torque (N.m)	Rated speed (rpm)	Rated current (A)	Encoder type
MF3 series	DC24	MF3S-40CS/CM30B(Z)1-201	100	0.32	3000	3	Magnetic encoder 17-bit
	DC48	MF3S-60CS/CM30B(Z)1-502	200	0.64	3000	5	
		MF3S-60CS/CM30B(Z)1-504	400	1.27	3000	10	
		MF3S-80CS/CM30B(Z)2-507	750	2.39	3000	20	
		MF3S-130CS/CM30B(Z)2-515	1500	4.8	3000	40	

Low Voltage Servo Matching List


Series	Power (W)	Servo motor	Matched driver	Encoder cable	Power cable
Low inertia DC24V	100	MF3S-40CS30B(Z)1-201	DF3E-0103	CP(T)-SP-M-Length	CM(T)-P07-Length
		MF3S-40CM30B(Z)1-201		CP(T)-SP-BM-Length	
Low inertia DC48V	200	MF3S-60CS30B(Z)1-502	DF3E-0205	CP(T)-SP-M-Length	CM(T)-P15-Length
		MF3S-60CM30B(Z)1-502		CP(T)-SP-BM-Length	
	400	MF3S-60CS30B(Z)1-504	DF3E-0410	CP(T)-SP-M-Length	CM(T)-V20-Length
		MF3S-60CM30B(Z)1-504		CP(T)-SP-BM-Length	
	750	MF3S-80CS30B(Z)2-507	DF3E-0720	CP(T)-SV-M-Length	CM(T)-XL60-Length
		MF3S-80CM30B(Z)2-507		CP(T)-SV-BM-Length	
		MF3S-130CS30BZ2-515	DF3E-1540	CP(T)-SC-M-Length	CMB(T)-XL60-Length
		MF3S-130CS30BZ2-515		CP(T)-SC-M-Length	
		MF3S-130CM30B2-515		CP(T)-SC-B-Length	
		MF3S-130CM30BZ2-515		CP(T)-SC-B-Length	

*Note: 400W and 750W brake motor need extra brake cable CB(T)-P03-Length.

Peripheral Wiring Diagram



Terminal Definition



CN0 port (E type)

Pin	Definition
1	CAN H
2	CAN L
3	CGND
4	485+
5	485-
6	GND

CN4 port (main circuit terminal)

Pin	Definition
1	PE
2	W
3	V
4	U
5	RB-
6	DC-
7	DC+/RB+
8	PE

*Note: RB+, RB- connect to external resistor.

CN1 port

Pin	Definition	Explanation
1	TXD	RS232 send
2	RXD	RS232 receive
3	GND	RS232 signal ground

CN3 port (communication encoder feedback)

Pin	Definition
1	5V
2	GND
3	/
4	/
5	485+
6	485-

CN2 port

Pin	Definition
1	P-
2	P+5V
3	P+24V
4	D-
5	D+5V
6	D+24V
7	SI1
8	SI2
9	SI3
10	SI4/+24VS
11	+24V
12	SO1
13	SO2
14	SO3
15	COM
16	-/GNDS

*Note: The terminal functions of CN2 are divided into two types. One is non-brake model. The function of terminal 10 is SI4 and terminal 16 is empty. The other is the brake model. The function of terminal 10 is +24VS and terminal 16 is GNDS, which can be used in braking control.

Terminal Definition

Set the communication station number of low-voltage servo through the dial switch SW1~SW6

Station no.	SW1	SW2	SW3	SW4	SW5	SW6
1	ON	OFF	OFF	OFF	OFF	OFF
2	OFF	ON	OFF	OFF	OFF	OFF
3	ON	ON	OFF	OFF	OFF	OFF
...	...	...	...	...	...	...
63	ON	ON	ON	ON	ON	ON
64	OFF	OFF	OFF	OFF	OFF	OFF

SW7, SW8 are used to control whether the internal terminal resistance of RS485 is turned on


RS485 internal terminal resistance		
SW7=ON	SW8=ON	ON
SW7=OFF	SW8=OFF	OFF

SW9, SW10 are used to control whether the internal terminal resistance of CANbus is turned on

CANbus internal terminal resistance		
SW9=ON	SW10=ON	ON
SW9=OFF	SW10=OFF	OFF


Typical Connection Diagram

P+ D, CW, CCW, AB phase interface circuit wiring diagram:




Torque Frequency Characteristic Curve


MF3S-60CS/CM30B1-504
MF3S-60CS/CM30BZ1-504



MF3S-80CS/CMB2-507
MF3S-80CS/CMBZ2-507



MF3S-130CS/CM30B2-515
MF3S-130CS/CM30BZ2-515



Specification Table

Driver specification

Item			DF3E-0103	DF3E-0205	DF3E-0410	DF3E-0720	DF3E-1540
Basic specification	Power		100W	200W	400W	750W	1500W
	Input power supply				DC24V-70V		
	Rated output current	Max continuous output current (Arms)	3	5	10	20	40
		Peak current (PEAK)	10	15	30	60	120
	Encoder feedback		17-bit communication encoder				
	Communication mode		RS232 / RS485 / CANopen				
	Using environ- ment	Ambient temperature	Operation: -10°C~40°C (no condensation) / storage: -20°C~60°C (no condensation)				
		Ambient humidity	Operation/storage: below 90%RH (no condensation)				
		Vibration and impact resistance	4.9m/s ² / 19.6m/s ²				
		Installation location	Places without dust, dry, vibration and corrosive substances				
		Installation method	Vertical or horizontal installation				
	Energy consumption braking		Can connect external brake resistor				
	Protection function		Overvoltage, undervoltage, overheating, overcurrent, overload, overspeed, excessive position deviation, output short circuit, encoder abnormality, regeneration abnormality protection, overtravel protection, oscillation protection, operation disconnection protection, etc				
Load change rate		0~100% load: below ±0.1% (at rated speed)					
Voltage change rate		Rated voltage ±10%: 0.01% (at rated speed)					
Temperature change rate		20±25°C: below ±0.1% (at rated speed)					
IO signal	Digital input specification		4 channels digital input (3 channels digital input for brake models)				
			Servo enable, alarm clear, no forward rotation, no reverse rotation, torque limit selection, internal speed selection, gear ratio switching, mode switching, pulse input prohibition, position deviation clear, internal position step change signal				
	Digital output specification		3 channels digital output				
			Positioning completed, servo ready, alarm output, speed arrival, rotation detection, torque limit output, same speed detection, brake release output				
Pulse direction		Support P+D, AB phase, CW/CCW					

Motor specification


Voltage level		DC48V		
Motor model MF		3S-60	3S-80	3S-130
		CS/CM30B(Z)1	CS/CM30B(Z)2	130CS/CM30B(Z)2
		504	507	515
		400	750	1500
Rated power (W)		10	19.2	40
Rated current (A)		3000	3000	3000
Rated speed (rpm)		3500	3500	3500
Max speed (rpm)		1.27	2.39	4.8
Rated torque (N.m)		3.81	7.17	14.4
Max torque (N.m)		358.4(374.9)	980(1030)	15018(15275)
Rotor inertia (10 ⁻⁴ kg.m ²)		≥1.3	≥2.5	≥15
Static friction torque (N.m)		74	147	300
Bearing axial force (N)		245	392	600
Bearing radial force (N)		Low inertia		
Inertia type		5		
Pole-pair number		17		
Encoder bit		Magnetism		
Encoder type		Natural cooling		
Cooling method		CLASSF(155°C)		
Motor insulation level		IP66		
Protection level		-15°C~+40°C (no freezing)		
Using environment	Ambient temperature	Relative humidity < 90% (no condensation)		
	Ambient humidity			

Installation Dimension Diagram


(Unit: mm)

Low voltage servo driver

DF3E-0720(Z)/ DF3E-0410(Z)




DF3E-1540(Z)




Low voltage servo motor


Motor model	Inertia type
MF3S-60CS/CM30B1-504	Low inertia




Motor model	Inertia type
MF3S-60CS/CM30BZ1-504	Low inertia




Motor model	Inertia type
MF3S-80CS/CM30B2-507	Low inertia




Motor model	Inertia type
MF3S-80CS/CM30BZ2-507	Low inertia



Motor model	Inertia type
MF3S-130CS/CM30B2-515	Low inertia



Motor model	Inertia type
MF3S-130CS/CM30BZ2-515	Low inertia



*Note: After the revision of 750W low-voltage servo motor, the body length is reduced.